

ATEN PREMIUM VP3520 5x2 presentation matrix switch



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : ATEN
Part number : VP3520
Caractéristiques :
HDCP : Y
AC input voltage : 110 - 220 V
Analog audio output terminal ports : 1
Built-in display : N
Cables included : AC
Depth : 432.4 mm
Extended display identification data (EDID) : Y
HDCP version : 2.2
HDMI input ports quantity : 3
HDMI output ports quantity : 1
Heat dissipation : 310 BTU/h
Heat dissipation (max) : 314 BTU/h
Height : 44 mm
High Dynamic Range (HDR) supported : Y
Housing colour : Black
IR receiver included : Y
Manual : Y
Maximum resolution (HDMI) : 4096 x 2160 pixels
Operating relative humidity (H-H) : 0 - 80%
Operating temperature (T-T) : 0 - 40 °C
Package depth : 515 mm
Package height : 155 mm
Package width : 338 mm
Power consumption (max) : 46.7 W

Power consumption (typical) : 45.8 W
Product type : Media presentation matrix switcher
Rack mount kit : Y
Relay outputs : 2
Remote control included : Y
RJ-45 input ports : 2
RJ-45 output ports : 1
RS-232 ports : 2
Rubber feet : Y
Storage temperature (T-T) : -20 - 60 °C
Supported resolutions : 4096 x 2160, 3840 x 2160, 1920 x 1080, 1920 x 1200, 1680 x 1050, 1600 x 1200, 1440 x 900, 1400 x 1050, 1280 x 1024, 1280 x 800, 1024 x 768, 800 x 600, 720 x 400, 640 x 480
Width : 272.3 mm