

DEXLAN Switch 6P 10/100 with 4 PoE+ 60W



DESCRIPTION

The DEXLAN 6-port PoE+ switch was designed for small CCTV systems. The housing is made of metal and the device is quite silent. It has 4 x RJ-45 PoE+ ports supplying 30 Watts to PoE cameras, or dual-band Wi-Fi hot-spots. The 2 additional RJ-45 ports can be used for Internet access and the connection of a network video recorder.

Product features:

- 4 x 10/100 PoE+ ports 30 W max EndSpan
- 2 x 100 Mbps RJ-45 Uplink ports - 150 m. max.
- Power supply included: 48 V / 60 W
- The power budget can be higher with a 48 V extra power supply plugged to the terminal block
- Includes 2 fixing kits (DIN/wallmount)
- Supported temperature range in operation: -10°C to 60°C
- IP-30 Aluminum housing
- 75 W optional power supply, please order PN 314647

TECHNICAL CHARACTERISTICS

Brand : DEXLAN

Part number : DX3082-P140

Main features :

Network standard : Gigabit

ODI Model Layer : Layer 2

Management : WEB+SNMP+RMON+CLI

Operating environment : SMB

Industrial : No

Rackmount : Yes

PoE function : Yes

Power supply : Embedded power supply

Outband console port : Yes

Temperature supported in operation : 0 to 50°C

Mounting system : 19» kit included

Connectors :

Total number of ports : 11

Number of RJ-45 ports : 9

Number of fiber ports : 2

Number of BNC Ethernet ports : 0

Other ports : No

RJ-45 patch cords :

Number of 10/100 ports : 0

Number of 10G ports : 0

Number of ports Multi-Gigabit 10/100/1G/2.5G/5G : 0

Number of Gigabit ports : 8

Fiber optics :

Number of 100FX ports : 0

Number of SFP Gigabit ports : 2

Number of SFP+ ports : 0

Number of ports QSFP 40G : 0

Number of SFP 1G/100 ports : 0

Number of SFP 100FX ports : 0

PoE data :

PoE standard : PoE+ 802,3at 30W

PoE budget (Watts) : 140

Number of 15-Watt PoE ports : 0

Number of 30-Watt PoE+ ports : 8

Number of 60-W PoE++ ports : 0

Dimensions :

Length (mm) : 280

Width (mm) : 180

Height (mm) : 44