



## DESCRIPTION

Sustainability is a key component of the RISE Series display lifts. Vogel's offers an endurance tested design of the display lift of over 30,000 cycles. No EPP/EPS is used in the packaging. There is also a reduction of 85% single used plastic in the packaging. This keeps waste streams to a minimum.

Top down assembly allows for a fast installation of Vogel's RISE display lifts. Various pre-assembled components are screw-mounted from above. An integrated cable management system (CIS®) allows for easy concealment of cabling during assembly. And with the ClickLoc system, you hear the certainty of a solid click when attaching the display to the frame. A software development kit is available upon request for software installation before or during setup.

## TECHNICAL CHARACTERISTICS

Brand : VOGEL'S

Part number : 7352050

### Design :

Certification : TÜV, CE

Cable management : Y

Depth : 846 mm

Height : 1205 mm

Height adjustment : Y

Lifting speed : 50 mm/sec

Maximum distance to floor : 186.7 cm

Maximum screen size : 2.18 m (86»)

Maximum VESA mount : 800 x 600 mm

Maximum weight capacity : 120 kg

Minimum distance to floor : 88.7 cm

Minimum screen size : 165.1 cm (65»)

Minimum VESA mount : 300 x 300 mm

Motorized : Y

Mounting : Freestanding

Mounting type : Floor

Number of displays supported : 1

Number of wheels : 4 wheel(s)

Panel mounting interface : 300 x 300,400 x 200,400 x 400,400 x 300,400 x 600,500 x 200,500 x 300,500 x 400,600 x 200,600 x 400,600 x 600,600 x 300,700 x 400,700 x 450,800 x 400,800 x 450,800 x 500,800 x 600

Product colour : Black

Quantity per pack : 1 pc(s)

Screws included : Y

Suitable for TV : Y

Width : 955 mm