



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : TP-LINK

Part number : ER7212PC

Connexion WAN :

Ethernet WAN : Y

DSL WAN : N

Caractéristiques :

Certification : CE, FCC, RoHS

3G/4G USB modem compatibility : N

AC adapter included : Y

Access Control List (ACL) : Y

Built-in processor : Y

Cabling technology : 10/100/1000Base-T(X)

Combo SFP ports quantity : 2

DC-in jack : Y

Depth : 131 mm

DHCP client : Y

DHCP server : Y

Ethernet interface type : Gigabit Ethernet

Ethernet LAN (RJ-45) ports : 10

Ethernet LAN data rates : 10,100,1000 Mbit/s

Flash memory : 4096 MB

Height : 35 mm

Housing material : Metal

Internal memory : 1024 MB

Internal memory type : DDR3

LED indicators : Y

Manual : Y

NAT functionality : Multi-Net NAT; Virtual Server; NAT-DMZ; FTP/H.323/SIP/IPSec/PPTP ALG; UPnP;
Networking standards : IEEE 802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
Operating relative humidity (H-H) : 10 - 90%
Operating temperature (T-T) : 0 - 45 °C
Output current : 2.43 A
Output voltage : 53.5 V
Port forwarding : Y
Power over Ethernet (PoE) : Y
Power over Ethernet (PoE) ports quantity : 8
Processor frequency : 1200 MHz
Product colour : Black
Reset button : Y
SFP WAN : Y
SIM card slot : N
Static route : Y
Storage relative humidity (H-H) : 5 - 90%
Storage temperature (T-T) : -40 - 70 °C
Supported protocols : TCP/IP, DHCP, ICMP, NAT, PPPoE, NTP, HTTP, HTTPS, DNS, IPSec, PPTP, L2TP, SNMP
Universal Plug and Play (UPnP) : Y
URL filtering : Y
VLAN support : Y
Width : 226 mm