

Hanwha camera 2MP ir bullet ir led 50 m XNO-6080RP/EX



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : XNO-6080R
Représentation / réalisation :
Type : IP security camera
Réseau :
Bluetooth : N
Back Light Compensation (BLC) : Y
Bit rate control : Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Built-in HDD : N
Camera shutter speed : 2 - 1/12000 s
Camera shutter type : Electronic
Card reader integrated : Y
Closest focusing distance : 0.5 m
Compatible memory cards : SD, SDHC, SDXC
Connectivity technology : Wired
Day/night mode : Y
Diameter : 9.1 cm
Ethernet interface type : Fast Ethernet
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Flip & mirror : Y
Focal length range : 2.8-12 mm
Form factor : Bullet
Frame rate : 30 fps
Highlight Compensation (HLC) : Y
Housing material : Aluminium
HTTPS encryption : Y

IK code : IK10
Infrared (IR) cut-off filter : Y
International Protection (IP) code : IP66
IP address filtering : Y
LED type : IR
Length : 368.6 mm
Lens viewing angle, diagonal : 142.1°
Lens viewing angle, horizontal : 119.5°
Lens viewing angle, vertical : 62.8°
Maximum aperture number : 1.4
Maximum memory card size : 512 GB
Maximum resolution : 1920 x 1080 pixels
Minimum aperture number : 3.6
Mounting type : Ceiling/wall
Networking standards : IEEE 802.1x, IEEE 802.3af
Night vision : Y
Night vision distance : 50 m
Number of cameras : 1
Number of effective pixels (H x V) : 1945 x 1097 pixels
Number of lenses : 1
Number of sensors : 1
Operating relative humidity (H-H) : 0 - 90%
Operating temperature (T-T) : -40 - 65 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8")
Placement supported : Outdoor
Power consumption (max) : 12 W
Power consumption (Power over Ethernet (PoE)) : 12.95 W
Power source type : DC, PoE
Privacy masking : Y
Product colour : Grey
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 90%
Storage temperature (T-T) : -50 - 60 °C
Streaming method : Multicast, Unicast
Supported network protocols : TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour
Total megapixels : 2 MP
Video compression formats : H.264, H.265, M-JPEG
Video motion detection : Y
Video streaming : Y
Voice codecs : G.711alaw, G.711ulaw, G.722.1, G.726, MP2L2
Weight : 2.18 kg
Wide Dynamic Range (WDR) : Y
Wi-Fi : N