

Eaton 3S 700 FR



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : 3S700F

Design :

Certification : CE/EAC/Ukr/Cm/CB report

AC outlets quantity : 8 AC outlet(s)

Automatic battery test : Y

Battery technology : Sealed Lead Acid (VRLA)

Cable length : 1.5 m

Cold start : Y

Depth : 170 mm

Harmonized System (HS) code : 85078000

Height : 86 mm

Hot-swap battery : N

Input frequency : 50/60 Hz

Input operation voltage (max) : 284 V

Input operation voltage (min) : 161 V

LED indicators : Y

Maximum current : 10 A

Nominal input voltage : 230 V

Operating altitude : 0 - 3000 m

Operating temperature (T-T) : 0 - 40 °C

Output frequency : 50 Hz

Output operation voltage (max) : 240 V

Output operation voltage (min) : 220 V

Output power : 420 W

Output power capacity : 0.7 kVA

Power protection features : Overdischarge

Product colour : Black, White

Safety : IEC 62040-1; IEC 62040-2 C2; IEC 62040-3; IEC 62040-4; IEC 61643-11

Surge protection : Y

UPS topology : Standby (Offline)

USB 2:0 ports quantity : 2

USB port : Y

Weight : 4 kg

Width : 335 mm