



DESCRIPTION

Brother TJ-4021TN Industrial Label Printer

4» industrial thermal label printer with touch panel display and print width up to 107mm

The Brother TJ-4021TN industrial label printer offers performance you can rely on when keeping up with increasing demand.

The high-volume thermal label printer has been designed to ensure minimal downtime and maximum productivity through fast print speeds, large ribbon capacity and in-built durability.

With ZPL2 emulation compatibility and a first-class user experience, the TJ-4021TN has been built with you in mind.

Connectivity as standard

USB, USB Host, Serial and Ethernet are included as standard for the industrial printers. An optional WLAN interface for WiFi connectivity is also available as an accessory to meet your requirements.

In-built durability

The TJ industrial printer series offers performance you can rely on, even in the toughest production environments. The reliable thermal barcode printer has been built with you in mind and built to last, ensuring you enjoy years of hassle-free label printing.

Integrate with ease

With the Brother TJ series, there is no need to worry about integration.

Our industrial printers support various printer command languages, including ZPL2 emulation, making printer replacements as easy as possible - with minimal disruption.

Maximise productivity

The TJ-4021TN label machine offers fast print speeds to help you keep up with increasing demand. The high volume label printer is

perfect for manufacturing and transport & logistics environments.

First-class user experience

Offering a touch panel display for instant feedback, the TJ-4021TN has been designed with the user in mind. Make life easy for your workers by troubleshooting issues in just a couple of taps.

TECHNICAL CHARACTERISTICS

Brand : BROTHER
Part number : TJ4021TNZ1
Built-in barcodes : AZTECCODE, CODABAR (NW-7), Code 128 (A/B/C), Code 39, Code 49, Code 93, Data Matrix, EAN128, EAN13, EAN8, GS1 DataBar, ITF-14, Industrial 2/5, Interleaved 2/5, MaxiCode, MicroPDF417, PDF417, QR Code, TLC39, UPC-E
Cables included : AC, USB
Colour : N
Colour display : Y
Connectivity technology : Wired
Control type : Buttons, Touch
Core diameter : 7.62 cm
Depth : 436 mm
Display diagonal : 8.89 cm (3.5»)
Ethernet LAN : Y
Flash memory : 128 MB
Harmonized System (HS) code : 84433210
Height : 274 mm
Internal memory : 128 MB
Languages support : Danish, German, Dutch, English, Spanish, Finnish, French, Italian, Norwegian, Portuguese, Swedish
LED indicators : Error, Power, Status
Linux operating systems supported : Y
Mac operating systems supported : Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina
Maximum label width : 12 cm
Maximum print length : 25.4 m
Maximum printing width : 10.7 cm
Maximum resolution : 203 x 203 DPI
Maximum roll diameter : 20.3 cm
Minimum print length : 5 mm
Mobile operating systems supported : Android, iOS
Number of fonts : 8
Operating relative humidity (H-H) : 25 - 85%
Operating temperature (T-T) : 0 - 40 °C
Page description languages : DPL, EPL2, ZPL II
Print speed : 254 mm/sec
Print technology : Direct thermal / Thermal transfer
Product colour : Black
Ribbon length : 450 m
Ribbon width : 4 cm
RS-232 ports : 1
Server operating systems supported : Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
Software development kit (SDK) : Y
Storage relative humidity (H-H) : 10 - 90%
Storage temperature (T-T) : -40 - 60 °C
USB port : Y

Weight : 9.4 kg
Width : 248 mm
Wi-Fi : N
Windows operating systems supported : Windows 10, Windows 8.1