



DESCRIPTION

PRODUCT INFORMATION

The PATCHBOX® Plus+ STP is the state of the art cable management system; fast, neat and installed in all-in-one solution. It replaces conventional cable management and patch cords completely with an all-in-one solution.

The PATCHBOX® Plus+ STP with its retractable cables, provides the user with the exact cable length needed. No more overly long cables, creating a cabinet full of cable spaghetti. Installation time is dramatically reduced and due to the clean setup maintenance can be done remotely further reducing costs.

PRODUCT FEATURES

- Cable: up to 1.7m/2.7m extractable patch cord, 100% tested
- Cassettes: with clip in frame function
- Cable stopper: keep the cable in the extracted length
- Labeling: directly label the cassettes (i.e. panel A13)
- Easy swapping: easily change cassettes
- Tool less: no tools needed at all
- Cable storage: store unused patch cords right within the cabinet

ITEMS INCLUDED

- 3pcs. Cassettes with Cat. 6 STP patch cords (component tested)

TECHNICAL INFORMATIONS

- Cable: Cat. 6 STP (unshielded), 250MHz, AWG36, 100% stranded copper, PVC jacket, 10Gbit ready
- Connector: RJ45 Unshielded Plug, Pins Gold plated, Snagless Booted
- Cable Length: 1.7m extractable (covers 26RU from mid-mid)
- Cable Length Long Range: 2.7m: 1.7m extractable/1m over length (covers 48RU from mid-mid)
- Cassette Profiles: Stainless Steel, laser-welded
- All Plastic Parts: Polyoxymethylene (POM)

- Mounting Rails: Stainless Steel, 500mm to 850mm from 19" rail to 19" rail
- Operating Temperature Range: +10°C to +45°C
- Ambient Humidity (non-condensing): 10% to 95%

Packaging Dimensions

- Depth: 693mm
- Height: 47mm
- Width: 65mm
- Weight: 1.05kg

Product complies with RoHS and CE
Designed in Austria. Made in Hungary.

TECHNICAL CHARACTERISTICS

Brand : PATCHBOX

Part number : C60SMAOS211X1Y

Caractéristiques :

Full duplex : Y

Certification : CE

Cable length : 1.8 m

Cable type : OFC

Cladding diameter : 125 µm

Connector 1 : LC

Connector 1 gender : Male

Connector 2 : LC

Connector 2 gender : Male

Connector material : Ceramic

Connector polish type : PC

Core diameter : 9 µm

Country of origin : Hungary

Data transfer rate : 100 Gbit/s

Ethernet interface type : 10 Gigabit Ethernet, 40 Gigabit Ethernet, 100 Gigabit Ethernet

Fiber mode structure : Single-mode

Fibre optic type : OS2

Insertion loss : 0.1 dB

Jacket material : Low smoke zero halogen (LSZH)

Material : Polyoxymethylene (POM), Stainless steel

Operating temperature (T-T) : 10 - 45 °C

Package depth : 690 mm

Package height : 50 mm

Package weight : 400 g

Package width : 50 mm

Product colour : Yellow

Quantity per pack : 1 pc(s)

Wavelengths supported : 1310,1550 nm