

BOSCH NIN-63023-A3



DESCRIPTION

This camera provides clear images 24/7 even at night or under low-light conditions.

The exceptional starlight sensitivity enables this camera to work with a minimum of ambient light. The extended dynamic mode provides detailed images in scenes with challenging lighting.

The camera is available in 1080p or 720p resolution versions and provides up to 60 images per second.

The aesthetic vandal-resistant housing makes the camera suitable for indoor or outdoor installation.

TECHNICAL CHARACTERISTICS

Brand : BOSCH

Part number : NIN-63023-A3

Représentation / réalisation :

Type : IP security camera

Système d'objectif :

Auto focus : Y

Vidéo :

Full HD : Y

Certification : CE, cULus, WEEE, RCM, EAC and China RoHS, UL

Alarm input/output : Y

Analog signal format system : NTSC, PAL

Angle of rotation : 270°

Audio formats supported : G.711, LC-AAC

Auto-tracking : Y

Back Light Compensation (BLC) : Y

Behavior analysis : Line crossing detection, Object removal detection

BNC output ports : 1

Cabling technology : 10/100Base-T(X)

Camera shutter speed : 1/25 - 1/15000 s

Camera shutter type : Electronic

Card reader integrated : Y

Compatible memory cards : MicroSDHC, MicroSDXC

Connectivity technology : Wired

Day/night mode : Y
DC output voltage : 12, 48
Diameter : 15.8 cm
Digital watermark : Y
Ethernet interface type : Fast Ethernet
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Flip & mirror : Y
Focal length range : 3 - 9 mm
Focus : Motorized
Fog proof : Y
Form factor : Dome
Frame rate : 60 fps
Height : 124 mm
Housing material : Aluminium
IK code : IK10
International Protection (IP) code : IP66
Lens viewing angle, horizontal : 117°
Lens viewing angle, vertical : 59°
Maximum memory card size : 2000 GB
Maximum resolution : 1920 x 1080 pixels
Mounting type : Ceiling
Networking standards : IEEE 802.3af, IEEE 802.3at
Night vision : Y
Noise reduction : Y
Number of cameras : 1
Number of effective pixels (H x V) : 1920 x 1080 pixels
Number of lenses : 1
Number of sensors : 1
Operating relative humidity (H-H) : 5 - 95%
Operating temperature (T-T) : -30 - 55 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Pan range : 0 - 360°
Placement supported : Indoor & outdoor
Power consumption (typical) : 7.2 W
Power source type : PoE
Privacy masking : Y
Product colour : Black, White
Protection features : Dust resistant, Splash proof
PTZ control : Y
Security algorithms : 3DES, DES, SSL/TLS
Sensor type : CMOS
Signal-to-Noise Ratio (SNR) : 55 dB
Storage relative humidity (H-H) : 0 - 98%
Storage temperature (T-T) : -50 - 70 °C
Streaming method : Multicast, Unicast
Supported graphics resolutions : 256 x 144, 352 x 240, 432 x 240, 512 x 288, 704 x 480, 768 x 432, 854 x 480 (WVGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1920 x 1080 (HD 1080)
Supported network protocols : IPv4, IPv6, UDP, TCP, HTTP, HTTPS, RTP/ RTCP, IGMP V2/V3, ICMP, ICMPv6, RTSP, FTP, ARP, DHCP, APIPA (Auto-IP, link local address), NTP (SNTP), SNMP (V1, V3, MIB-II), 802.1x, DNS, DNSv6, DDNS (DynDNS.org, selfHOST.de, no-ip.com), SMTP, iSCSI, UPnP (SSDP), DiffServ (QoS), LLDP, SOAP, Dropbox, CHAP, digest authentication
Supported video modes : 720p, 1080p
Sustainability certificates : RoHS

Tilt angle range : 0 - 90°
Total megapixels : 2 MP
Video compression formats : H.264, M-JPEG
Video streaming : Y
Voice codecs : G.711
Weight : 850 g
White balance : Auto, Manual, Sodium lamp
Wide Dynamic Range (WDR) : Y
Zoom capability : Y