

ATEN KL1508AM 8-Port Cat 5 Dual Rail 17" LCD KVM switch



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : ATEN
Part number : KL1508AM-AXA-FG
AC input frequency : 50 - 60 Hz
AC input voltage : 100 - 240 V
Built-in display : Y
Console ports : PS/2, USB A, VGA (D-Sub)
Console USB ports quantity : 2
Depth : 701.2 mm
Display : LCD
Display diagonal : 43.2 cm (17»)
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 8
Harmonized System (HS) code : 85176200
HD type : WUXGA
Height : 44 mm
Hot keys : Y
Housing material : Metal
Input current : 1 A
Keyboard port type : USB, PS/2
LED indicators : Y
Manual : Y
Master (outer) case gross weight : 18.7 kg
Master (outer) case height : 135 mm
Master (outer) case length : 833 mm
Master (outer) case net weight : 15.5 kg
Master (outer) case width : 668 mm
Maximum resolution : 1920 x 1200 pixels

Mouse port type : USB, PS/2
Number of computers controlled : 8
On Screen Display (OSD) : Y
Operating relative humidity (H-H) : 0 - 80%
Operating temperature (T-T) : 0 - 40 °C
Package depth : 833 mm
Package height : 135 mm
Package weight : 18.7 kg
Package width : 668 mm
Power source : AC
Product colour : Black
Products per master (outer) case : 1 pc(s)
PS/2 ports quantity : 2
Push button : Y
Quick installation guide : Y
Rack capacity : 1U
Rack mounting : Y
Scan interval : 1,255 s
Storage relative humidity (H-H) : 0 - 80%
Storage temperature (T-T) : -20 - 60 °C
USB connector type : USB Type-A
Video bandwidth : 60 Hz
Video port type : VGA
Weight : 15.5 kg
Width : 480 mm