



DESCRIPTION

Brothers TD-4420TN Thermal Transfer Label and Receipt printer provides the media flexibility, longevity and cost efficiency required for high volume printing at 203dpi resolution. This versatile device is ready to print on a wide range of media for barcodes, receipts and labels along with easy integration with the applications and database systems you rely on with ZPLII emulation, SAP & Bartender compatibility. Supporting a wide range of media to meet the needs of your operation, whether its longevity, abrasion resistance or even colour, the TD-4420TN offers the required flexibility thats important to your commercial or industrial operation.

TECHNICAL CHARACTERISTICS

Brand : BROTHER
Part number : TD-4420TN
Connectivité :
Bluetooth : N
AC adapter included : Y
AC adapter output current : 2 A
AC input frequency : 50/60 Hz
AC input voltage : 100 - 240 V
Built-in barcodes : GS1 DataMatrix, AZTECCODE, CODABAR (NW-7), Code 11, Code 128 (A/B/C), Code 39, Code 49, Code 93, EAN128, EAN13, EAN8, GS1 DataBar, ITF-14, Interleaved 2/5, LOGMARS, MSI, MaxiCode, MicroPDF417, PDF417, PLESSEY, POSTNET, QR Code, UPC-A, UPC-E
Cables included : AC, USB
Colour : N
Connectivity technology : Wired
Core diameter : 2.54 cm
Depth : 280 mm
Display : N
Ethernet LAN : Y
Flash memory : 128 MB
Harmonized System (HS) code : 84433210
Height : 177.5 mm
Internal memory : 64 MB
Languages support : Danish, German, Dutch, English, Spanish, Finnish, French, Italian, Norwegian, Portuguese, Swedish
LED indicators : Y

Linux operating systems supported : Y
Mac operating systems supported : Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave
Maximum label width : 11.2 cm
Maximum print height : 10.8 cm
Maximum print length : 25.4 m
Maximum resolution : 203 x 203 DPI
Maximum roll diameter : 12.7 cm
Number of fonts : 8
Number of languages : 11
Operating relative humidity (H-H) : 5 - 40%
Operating temperature (T-T) : 10 - 90 °C
Page description languages : DPL, EPL, ZPL, ZPL II
Print speed : 6 lpm
Print technology : Direct thermal / Thermal transfer
Product colour : Black
Quantity per pack : 1 pc(s)
Quick start guide : Y
RS-232 ports : 1
Server operating systems supported : Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
Software development kit (SDK) : Y
Starter roll included : Y
Storage relative humidity (H-H) : 25 - 85%
Storage temperature (T-T) : -40 - 60 °C
USB 2:0 ports quantity : 2
USB port : Y
Warranty card : Y
Weight : 2.5 kg
Width : 204 mm
Wi-Fi : N
Windows operating systems supported : Windows 10, Windows 7, Windows 8, Windows 8.1