

93PS-30(40)-30-0-MBS-6



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : EATON	
Part number : BD03A0306A01100000	
Design :	
Certification :	IEC 62040-2, IEC 62040-3
Battery life (max) :	10 year(s)
Battery technology :	Sealed Lead Acid (VRLA)
Battery voltage :	384 V
Depth :	750 mm
Display type :	LCD
Efficiency :	96%
Form factor :	Tower
Height :	1750 mm
Hot-swap battery :	Y
Input current Total Harmonic Distortion (THD) :	4%
Input frequency :	50/60 Hz
Input frequency converter :	Y
Input operation voltage (max) :	415 V
Input operation voltage (min) :	220 V
Input power factor :	0.99
International Protection (IP) code :	IP20
LED indicators :	Y
Noise level :	60 dB
Number of batteries supported :	32
Number of input phases :	3
Number of output phases :	3
Output frequency :	50/60 Hz
Output operation voltage (max) :	415 V

Output operation voltage (min) : 220 V
Output power : 30000 W
Output power capacity : 30 kVA
Overload capacity (1 minute) : 125%
Overload capacity (10 minutes) : 110%
Power protection features : Overload
Product colour : Black
RS-232 ports : 1
Safety : IEC 62040-1
Total Harmonic Distortion (THD) (linear load) : 1%
Total Harmonic Distortion (THD) (non-linear load) : 5%
UPS topology : Double-conversion (Online)
USB port : Y
Width : 480 mm