



DESCRIPTION

The AeroPTZ is an environmentally rugged camera designed to meet extreme weather conditions. Using the latest aerodynamic technology and salt-air corrosion resistant glass ber body, the AeroPTZ can withstand the beating from tropical storms, extreme hot and cold temperatures, and gale-force winds.

Additionally, a unique i-PRO Video Stability Augment System (SAS) delivers superior, high-class hybrid image stabilization for extreme scenes with vibration. Making the AeroPTZ well-suited for ports, cities, highway, transit, airports and other outdoor mission critical environments where failure is not an option

TECHNICAL CHARACTERISTICS

Brand : PANASONIC

Part number : WV-SUD638-H

Représentation / réalisation :

Type : IP security camera

Réseau :

Bluetooth : N

Vidéo :

Full HD : Y

Connectivité :

Interface : RJ-45

AC input frequency : 50 - 60 Hz

AC input voltage : 100 - 240 V

Alarm input/output : Y

Audio formats supported : AAC-LC, G.711, G.726

Auto pan mode : Y

Auto patrol mode : Y

Automatic gain control : Y

Auto-tracking : Y

Back Light Compensation (BLC) : Y

Built-in HDD : N

Camera shutter speed : 1/60 - 1/10000, 1/30 - 1/10000 s

Card reader integrated : Y

Closest focusing distance : 2 m
Compatible memory cards : MicroSD (TransFlash)
Connectivity technology : Wired
Day/night mode : Y
Depth : 266 mm
Digital zoom : 4x
Dynamic range : 105 dB
Ethernet interface type : Fast Ethernet
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Focal length range : 4.3 - 129 mm
Frame rate : 60 fps
Headphone outputs : 1
Height : 450 mm
Highlight Compensation (HLC) : Y
Housing material : Glass-reinforced plastic (GRP)
IK code : IK10
Image stabilizer : Y
Infrared (IR) cut-off filter : Y
International Protection (IP) code : IP67
Maximum aperture number : 1.6
Maximum resolution : 1920 x 1080 pixels
Microphone in : Y
Mobile operating systems supported : Android, iOS
Mounting type : Ceiling/wall
Noise reduction : Y
Number of cameras : 1
Number of users : 14 user(s)
Operating relative humidity (H-H) : 10 - 100%
Operating temperature (T-T) : -50 - 60 °C
Optical sensor size : 25.4 / 3 mm (1 / 3»)
Optical zoom : 45x
Pan preset speed : 200 °/sec
Pan range : -180 - 180°
Pan speed : 100 °/sec
Placement supported : Outdoor
Power source type : AC
Preset points : Y
Privacy protection : Y
Product colour : Grey
Protection features : Dust resistant, Snow resistant, Vibration proof, Water resistant
PTZ control : Y
Sensor type : MOS
Streaming method : Multicast, Unicast
Supported graphics resolutions : 1280 x 720 (HD 720), 1920 x 1080 (HD 1080)
Supported network protocols : IPv6 : TCP/IP, UDP/IP, HTTP, HTTPS, RTP, FTP, SMTP, DNS, NTP, SNMP, DHCPv6, MLD, ICMP, ARP, IEEE 802.1X, DiffServ
Supported video modes : 720p, 1080p
Tilt angle range : -45 - 90°
Tilt preset speed : 200 °/sec
Tilt speed : 100 °/sec
Video compression formats : H.264
Video formats supported : H.264
Video motion detection : Y

Voice codecs : G.711, G.726

Weight : 8.5 kg

Wide Dynamic Range (WDR) : Y

Width : 220 mm

Wi-Fi : N

Zoom capability : Y