



DESCRIPTION

Optimized for use with the EX-1280C, the EX-UH Dante endpoint, is a convenient, cost effective solution for connecting remote BYOD devices or telephone handsets over a single cat-5/6 cable. Whether used under a conference table to connect a laptop running a softcodec such as Skype for Business, or to connect a customer's handset for bridging calls, or both, the EX-UH's high-quality USB and headset to Dante audio conversion simplifies wiring and adding extra codecs to a conferencing system. Autodiscovery, drag and drop programming, and auto-routing in ControlSpace Designer make connecting the EX-UH easy.

- One-cable-from-the-table connectivity supports PoE+ and Dante audio networking to maximize ease of integration
- Dante audio networking for connection to other Dante-enabled products over Ethernet-based networks.
- USB 2.0 connector supports PC connections to soft codecs such as Skype for Business
- Headset connectors for direct connection to office and mobile phones through RJ-9 and 3.5 mm TRRS ports
- Dual network and power connectors allow daisy-chaining of multiple EX endpoints
- Rotatable mounting tabs allow for multiple mounting options
- Low-profile aluminum enclosure with integrated LED indicators for unobtrusive under-table mounting
- Simplified software configuration via ControlSpace Designer software. Supports autodiscovery, auto-routing, and logic presets for microphone LEDs and pushbuttons
- Optional magnetic mounting plate for single-handed under-table mounting, and a 60 W power supply
- Power and signal indicators

TECHNICAL CHARACTERISTICS

Brand : BOSE

Part number : 771784-0110

Audio input : Micro-B type, RJ-9, 3.5 mm TRRS

Built-in display : N

Channels quantity : 4 channels

DC input voltage : 12 V

Depth : 92 mm

Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 2

Frequency range : 20 - 20000 Hz

Height : 29 mm

LED indicators : Power

Microphone included : N

Operating temperature (T-T) : 0 - 40 °C

Power consumption (typical) : 5 W

Product colour : Black

Rack mounting : N

Standard interfaces : USB

USB 2:0 ports quantity : 1

USB connector type : Micro-USB B

Width : 214 mm