

DAHUA- Switch PFS4226-24ET-240



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : DAHUA TECHNOLOGY
Part number : DH-PFS4226-24ET-240
Réseau :
Full duplex : Y
10G support : N
AC input voltage : 100 - 240 V
Authentication : Port-based authentication
Authentication type : IEEE 802.1x, RADIUS
Basic switching RJ-45 Ethernet ports quantity : 24
Basic switching RJ-45 Ethernet ports type : Fast Ethernet (10/100)
Combo SFP ports quantity : 2
Copper ethernet cabling technology : 10BASE-T, 100BASE-TX, 1000BASE-T
Depth : 300 mm
DHCP features : DHCP client
Fast Ethernet (copper) ports quantity : 24
Fiber ethernet cabling technology : 1000BASE-X
Flow control support : Y
Form factor : 1U
Forwarding rate : 6.55 Mpps
Height : 44 mm
IP-MAC-Port binding : Y
LED indicators : Y
MAC address table : 4000 entries
Management protocols : SNMP V1/V2C/V3
Networking standards : IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
Operating relative humidity (H-H) : 10 - 90%

Operating temperature (T-T) : -10 - 55 °C
Port mirroring : Y
Power over Ethernet (PoE) : Y
Power over Ethernet (PoE) ports quantity : 24
Product colour : Black
Quality of Service (QoS) support : Y
Rack mounting : Y
Spanning tree protocol : Y
Switch layer : L2
Switch type : Managed
Switching capacity : 8.8 Gbit/s
System event log : Y
Total Power over Ethernet (PoE) budget : 240 W
VLAN support : Y
Web-based management : Y
Weight : 3.51 kg
Width : 440 mm