

HANWHA IP camera QNO-6030R



DESCRIPTION

The QNO-6030R from Hanwha’s Q Series affordable network camera line is a 2MP bullet network camera featuring WiseStream, Hanwha’s compression technology, triple codec H.265/H.264/MJPEG, 6.0mm lens, IR, IP66, IK10, PoE/12VDC, 120dB True WDR, Defocus Detection, Hallway View, one-way audio and SD card slot (SD/SDHC/SDXC up to 128GB).

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : QNO-6030R
Représentation / réalisation :
Type : IP security camera
Réseau :
Bluetooth : N
Vidéo :
Full HD : Y
Connectivité :
Interface : RJ-45
Alarm input/output : Y
Built-in HDD : N
Card reader integrated : Y
Compatible memory cards : SD, SDHC, SDXC
Connectivity technology : Wired
Day/night mode : Y
Diameter : 7 cm
Ethernet interface type : Fast Ethernet
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Fixed focal length : 6 mm
Flip & mirror : Y
Form factor : Bullet
Frame rate : 30 fps
Height : 246 mm

Housing material : Metal
IK code : IK10
International Protection (IP) code : IP66
LED type : IR
Lens viewing angle, diagonal : 61.14°
Lens viewing angle, horizontal : 52.24°
Lens viewing angle, vertical : 28.86°
Maximum aperture number : 1.8
Maximum memory card size : 128 GB
Maximum resolution : 1920 x 1080 pixels
Mounting type : Ceiling/Pole
Networking standards : IEEE 802.3af
Night vision : Y
Night vision distance : 20 m
Noise reduction : Y
Number of cameras : 1
Number of effective pixels (H x V) : 1984 x 1105 pixels
Number of users : 6 user(s)
Operating relative humidity (H-H) : 0 - 90%
Operating temperature (T-T) : -30 - 55 °C
Optical sensor size : 25.4 / 2.9 mm (1 / 2.9")
Placement supported : Outdoor
Power consumption (max) : 6 W
Power consumption (Power over Ethernet (PoE)) : 7 W
Power source type : PoE
Privacy masking : Y
Product colour : Grey, Metallic
Progressive scan : Y
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 90%
Storage temperature (T-T) : -30 - 60 °C
Streaming method : Multicast, Unicast
Supported graphics resolutions : 320 x 240, 640 x 480 (VGA), 720 x 576, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080)
Supported network protocols : TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour
Total megapixels : 2 MP
Video compression formats : H.264, H.265, M-JPEG
Video motion detection : Y
Voice codecs : G.711, G.711u, G.726
Weight : 730 g
White balance : ATW, AWC, Indoor, Manual, Outdoor
Wide Dynamic Range (WDR) : Y
Wi-Fi : N