



DESCRIPTION

The ProLite T1633MSC-B1 uses projective capacitive touch technology, built into an eye catching bezel with edge-to-edge glass. The screen guarantees high durability, scratch-resistance, clarity and a perfect picture performance. Featuring IPS Panel Technology and Full HD (1920x1080) resolution, it offers natural, highly accurate colours and wide viewing angles. The flexible stand can be positioned at several angles creating a comfortable and ergonomic user experience and the integrated cable management system hides all the cables and electrical wires giving a neat and cable-free workspace. In addition to the superb image quality, the screen comes with an IP54 rating, which means the screen and bezel is dust and water resistant from the front. A perfect solution for retail applications.

TECHNICAL CHARACTERISTICS

Brand : IIYAMA
Part number : T1633MSC-B1
Représentation / réalisation :
NVIDIA G-SYNC : No
AMD FreeSync : No
Connectivité :
HDMI : Yes
Design :
Certification : CE, TÜV-Bauart, EAC, RoHS, ErP, WEEE, REACH, UKCA
HDCP : Yes
AC input frequency : 50/60 Hz
AC input voltage : 100 - 240 V
Built-in camera : No
Built-in speaker(s) : Yes
Built-in USB hub : Yes
Cable lock slot : Yes
Cable lock slot type : Kensington
Cables included : AC, HDMI, USB
Contrast ratio (typical) : 1000:1
Depth (with stand) : 200 mm
Display brightness (typical) : 450 cd/m ²

Display diagonal : 39.6 cm (15.6»)
Display number of colours : 16.7 million colours
Display resolution : 1920 x 1080 pixels
Display technology : LCD
DisplayPorts quantity : 1
Energy consumption (SDR) per 1000 hours : 8 kWh
Energy efficiency class (SDR) : C
Energy efficiency scale : A to G
European Product Registry for Energy Labelling (EPREL) code : 1629639
HD type : Full HD
HDMI ports quantity : 1
Height (with stand) : 284 mm
Height adjustment : No
Horizontal scan range : 30 - 68 kHz
International Protection (IP) code : IP54
Market positioning : Home
Maximum refresh rate : 60 Hz
Native aspect ratio : 16:9
Number of OSD languages : 12
Number of speakers : 2
On Screen Display (OSD) : Yes
On Screen Display (OSD) languages : Traditional Chinese, Czech, German, Dutch, English, Spanish, French, Italian, Japanese, Polish, Portuguese, Russian
Package depth : 169 mm
Package height : 343 mm
Package type : Box
Package weight : 5.3 kg
Package width : 475 mm
Panel mounting interface : 100 x 100 mm
Panel type : IPS
Pixel pitch : 0.179 x 0.179 mm
Power adapter included : Yes
Power consumption (off) : 0.5 W
Power consumption (standby) : 8 W
Power consumption (typical) : 12 W
Power supply type : External
Product colour : Black
Quick start guide : Yes
Response time : 5 ms
RMS rated power : 4 W
Screen shape : Flat
Tilt angle range : 90 - 5°
Touchscreen : Yes
Touchscreen technology : Projected capacitive system
VESA mounting : Yes
Viewable size, horizontal : 34.4 cm
Viewable size, vertical : 19.4 cm
Viewing angle, horizontal : 178°
Viewing angle, vertical : 178°
Weight (with stand) : 3.4 kg
Width (with stand) : 389 mm