

HANWHA- Camera ANV-L6012R



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : ANV-L6012R
Représentation / réalisation :
Type : IP security camera
Réseau :
Bluetooth : No
Alert notification type : E-mail
Anti-flicker : Yes
Back Light Compensation (BLC) : Yes
Bit rate control : Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Built-in HDD : No
Camera pan control : Yes
Camera shutter speed : 2~1/12000 s
Camera shutter type : Electronic
Camera tilt control : Yes
Card reader integrated : Yes
Compatible memory cards : MicroSD (TransFlash), SDHC
Connectivity technology : Wired
Day/night mode : Yes
Detect distance : 25.1 m
Diameter : 12 cm
Digest authentication : Yes
Ethernet interface type : Fast Ethernet
Ethernet LAN : Yes
Ethernet LAN (RJ-45) ports : 1
Fixed focus : Yes
Flash memory : 256 MB

Flip & mirror : Yes
Focal length range : 2.8 mm
Form factor : Dome
Frame rate : 30 fps
Height : 91.7 mm
Housing material : Aluminium, Plastic
Identify distance : 2.5 m
IK code : IK10
International Protection (IP) code : IP66
Languages support : English
LED type : IR
Lens diameter : 2.8 mm
Lens viewing angle, diagonal : 134.4°
Lens viewing angle, horizontal : 113.7°
Lens viewing angle, vertical : 61.5°
Live view : Yes
Maximum aperture number : 2
Maximum memory card size : 32 GB
Maximum resolution : 1920 x 1080 pixels
Mirror : Yes
Mounting type : Ceiling
Night vision : Yes
Night vision distance : 30 m
Noise reduction : Yes
Noise reduction technology : Smart Super Noise Reduction (SSNR)
Number of cameras : 1
Number of lenses : 1
Number of sensors : 1
Number of simultaneous live view channels : 3 channels
Number of users : 6 user(s)
Observe distance : 10 m
Operating temperature (T-T) : -30 - 55 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8")
Pan range : 0 - 350°
Placement supported : Indoor & outdoor
Power consumption (max) : 6.4 W
Power consumption (Power over Ethernet (PoE)) : 5 W
Power source type : PoE
Privacy masking : Yes
Product colour : White
Quality of Service (QoS) support : Yes
RAM capacity : 512 MB
Recognize distance : 5 m
Remotely operated : Yes
Security algorithms : EAP-LEAP, EAP-TLS, HTTPS
Sensor type : CMOS
Storage temperature (T-T) : -30 - 55 °C
Streaming method : Multicast, Unicast
Supported graphics resolutions : 1280 x 960, 1280 x 1024 (SXGA), 720 x 480, 720 x 576, 800 x 600 (SVGA), 800 x 448, 1024 x 768 (XGA), 1920 x 1080 (HD 1080), 640 x 480 (VGA), 640 x 360, 1280 x 720 (HD 720)
Supported network protocols : IPv4, IPv6
Tilt angle range : 0 - 67°
Total megapixels : 2 MP

Video compression formats : H.264, H.265, M-JPEG
Video motion detection : Yes
Video streaming : Yes
Weight : 410 g
White balance : ATW, AWC, Indoor, Manual, Outdoor
Wide Dynamic Range (WDR) : Yes
Wi-Fi : No