

# 8-Port USB True 4K DisplayPort KVM Switch with USB 3.0



## DESCRIPTION

The ATEN CS19208 8-Port USB 3.0 4K DisplayPort KVM Switch can effectively access and control up to 8 DisplayPort computers from a single USB keyboard, USB mouse, and monitor console. With its dual interface console, users can choose between DisplayPort/HDMI video output supporting high video quality up to 4K DCI (4096 x 2160 @ 60Hz), presenting crystal-clear visuals.

1x CS19208 8-Port USB 3.0 4K DisplayPort KVM Switch with Rack Mounting Kit

2x LIN5-20K1-K13G DisplayPort 1.4 Cables

2x LIN6-11C1-E12G USB 3.0 Cables

2x LIN5-0205-21CG Audio Cables

1x LIN5-04A2-J11G Firmware Upgrade Cable

1x 0X02-0017-000G Foot Pad Set (4 pcs)

1x 0AD8-8012-33MG + LIN2-418K-E12G Power Adapter

1x User Instructions

## TECHNICAL CHARACTERISTICS

Brand : ATEN

Part number : CS19208-AT-G

Audio connections : Y

Built-in display : N

Console ports : 3.5mm headphone, DisplayPort, HDMI, USB A

Console USB ports quantity : 2

DC input voltage : 12 V

DC-in jack : Y

Depth : 214.3 mm

DisplayPorts quantity : 8

Harmonized System (HS) code : 85176200

HD type : 4K Ultra HD

Headphone outputs : 9

Height : 44 mm

Hot keys : Y

Housing material : Metal

Keyboard port type : USB

LED indicators : Y
Manual : Y
Master (outer) case gross weight : 15.6 kg
Master (outer) case height : 348 mm
Master (outer) case length : 519 mm
Master (outer) case net weight : 11.2 kg
Master (outer) case width : 427 mm
Maximum resolution : 4096 x 2160 pixels
Mouse port type : USB
Number of computers controlled : 8
Number of microphone inputs : 1
Operating relative humidity (H-H) : 0 - 80%
Operating temperature (T-T) : 0 - 40 °C
Package depth : 499 mm
Package height : 324 mm
Package weight : 4.83 kg
Package width : 133 mm
Power consumption (typical) : 18.44 W
Product colour : Black
Products per master (outer) case : 3 pc(s)
Push button : Y
Quick installation guide : Y
Scan interval : 1,5,255 s
Storage relative humidity (H-H) : 0 - 80%
Storage temperature (T-T) : -20 - 60 °C
USB 3:2 Gen 1 (3:1 Gen 1) Type-A hub ports quantity : 2
USB 3:2 Gen 1 (3:1 Gen 1) Type-B ports quantity : 8
USB connector type : USB Type-A, USB Type-B
USB hub : Y
Video bandwidth : 60 Hz
Video port type : DisplayPort
Weight : 3.75 kg
Width : 432.4 mm