

Allied AT-GS950/10PS switch 8 ports gigabit poe+ & 2 sfp



DESCRIPTION

The Allied Telesis AT-GS950/10PS Gigabit Ethernet WebSmart switch features two Gigabit ports, two SFP combo ports, and eight PoE+ ports delivering up to 30 Watts per port to support video surveillance and security cameras, wireless access points, IP phones and other PoE powered devices. The PoE option eliminates the need for power rewiring and minimizes the clutter of power supplies and adapters in awkward places. Thanks to its compact size, the AT-GS950/10PS is ideal for wiring-constrained and smaller environments such as micro branch offices, classrooms, cafes, and smaller retail stores.

TECHNICAL CHARACTERISTICS

Brand : ALLIED TELESIS
Part number : AT-GS950/10PS-50
Main features :
Network standard : Gigabit
ODI Model Layer : Layer 2
Management : Web Browser
Operating environment : SMB
Industrial : No
Rackmount : Yes
PoE function : Yes
Power supply : Embedded power supply
Outband console port : No
Temperature supported in operation : 0 to 50°C
Mounting system : Optional kit
Connectors :
Total number of ports : 10
Number of RJ-45 ports : 8
Number of fiber ports : 2
Number of BNC Ethernet ports : 0
Other ports : 0
RJ-45 patch cords :
Number of 10/100 ports : 0
Number of 10G ports : 0

Number of Gigabit ports : 8
Fiber optics :
Number of 100FX ports : 0
Number of SFP Gigabit ports : 2
Number of SFP+ ports : 0
Number of SFP 1G/100 ports : 0
Number of SFP 100FX ports : 0
PoE data :
PoE standard : PoE+ 802,3at 30W
PoE budget (Watts) : 75
Number of 15-Watt PoE ports : 0
Number of 30-Watt PoE+ ports : 8
Number of 60-W PoE++ ports : 0
Dimensions :
Length (mm) : 330
Width (mm) : 200
Height (mm) : 44