

Tp-link archer MR400 4G lte modem wireless AC1200



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : TP-LINK
Part number : ARCHER MR400
Sécurité :
Stateful Packet Inspection (SPI) : Y
Réseau :
Dynamic DNS (DDNS) : Y
Connexion WAN :
Ethernet WAN : Y
Caractéristiques :
Certification : CE, RoHS
2G standards : Edge, GPRS, GSM
3G standards : DC-HSPA+, HSPA, HSPA+, UMTS
3G/4G USB modem compatibility : Y
4G bands supported : 800,900,1800,2100,2600 MHz
4G standard : LTE
AC adapter included : Y
Access Control List (ACL) : Y
Antenna design : Internal & external
Antennas quantity : 2
Cables included : LAN (RJ-45)
Cabling technology : 10/100Base-T(X)
Depth : 124.5 mm
Detachable antenna(s) : Y
DHCP client : Y
DHCP server : Y
DoS attack prevention : Y
Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 3
Ethernet LAN data rates : 10,100 Mbit/s
Ethernet LAN interface type : Fast Ethernet
Firewall : Y
GSM bands supported : 850,900,1800,1900 MHz
Guest access : Y
Height : 33.5 mm
LED indicators : LAN, Power, Status, WLAN
Linux operating systems supported : Y
Mac compatibility : Y
Mac operating systems supported : Y
Mobile network generation : 4G
Networking standards : IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
On/off switch : Y
Operating relative humidity (H-H) : 10 - 90%
Operating temperature (T-T) : 0 - 40 °C
Output current : 1.5 A
Output voltage : 12 V
Package depth : 223 mm
Package height : 70 mm
Package type : Box
Package width : 307 mm
Port forwarding : Y
Power source type : DC
Product colour : Black
Product type : Tabletop router
Quality of Service (QoS) support : N
Quick installation guide : Y
Reset button : Y
Security algorithms : 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK
SIM card slot : Y
Storage relative humidity (H-H) : 5 - 90%
Storage temperature (T-T) : -40 - 70 °C
Supported network protocols : IPv4, IPv6
Top Wi-Fi standard : Wi-Fi 5 (802.11ac)
Transmit power : <20dBm(2.4GHz), <23dBm(5GHz)
UMTS bands supported : 900,2100 MHz
USB port : N
VPN Passthrough : Y
VPN support : PPTP, L2TP, IPSec
VPN tunnels quantity : 10
Wall mountable : Y
Web-based management : Y
Width : 174 mm
Wi-Fi band : Dual-band (2.4 GHz / 5 GHz)
Wi-Fi standards : 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
Windows operating systems supported : Windows 10, Windows 2000, Windows 7, Windows 8, Windows 8.1, Windows 98SE, Windows NT, Windows Vista, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
WLAN data transfer rate (first band) : 450 Mbit/s
WLAN data transfer rate (max) : 867 Mbit/s
WLAN data transfer rate (second band) : 867 Mbit/s
WPS push button : Y