

Allied AT-GS950/16PS switch 8 ports gigabit poe+ & 2 sfp



DESCRIPTION

The Allied Telesis AT-x310-26FP features 24 Fast Ethernet ports with 2 Gigabit uplinks and 2 stacking ports. Power over Ethernet Plus (PoE+) provides up to 30 watts to support high power connected devices such as multi-band wireless access points and Pan, Tilt, and Zoom digital security cameras.

TECHNICAL CHARACTERISTICS

Brand : ALLIED TELESIS

Part number : AT-X310-26FP-50

Main features :

Network standard : Gigabit

ODI Model Layer : Layer 3

Management : WEB+SNMP+RMON+CLI

Operating environment : Professional

Industrial : No

Rackmount : Yes

PoE function : Yes

Power supply : Embedded power supply

Outband console port : Yes

Temperature supported in operation : 0 to 50°C

Mounting system : 19» kit included

Connectors :

Total number of ports : 32

Number of RJ-45 ports : 26

Number of fiber ports : 4

Number of BNC Ethernet ports : 0

RJ-45 patch cords :

Number of 10/100 ports : 24

Number of 10G ports : 0

Number of Gigabit ports : 2

Fiber optics :

Number of 100FX ports : 0

Number of SFP Gigabit ports : 0

Number of SFP+ ports : 2

Number of SFP 1G/100 ports : 2

Number of SFP 100FX ports : 0

PoE data :

PoE standard : PoE+ 802,3at 30W

PoE budget (Watts) : 370

Number of 15-Watt PoE ports : 0

Number of 30-Watt PoE+ ports : 24

Number of 60-W PoE++ ports : 0

Dimensions :

Length (mm) : 440

Width (mm) : 360

Height (mm) : 44