



DESCRIPTION

Choose non-stop high performance and reliability with the ideal all-in-one signage solution for mission critical environments. The LH7554UHS from iiyama is a 500cd/m² high brightness professional large format display and can be operated in landscape or portrait orientation in continual around the clock environments 24/7 without any interruption. Its versatility can be adapted to your industry display needs.

The on-board CMS (Content Management Software) gives you total control of your messaging and advertising remotely and safely. The SDM Slot provides embedded PC option for total flexibility, security and control, while the Signal FailOver feature ensures your content is always actively displayed through your choice of inputs. WiFi enabled, this series is ready for remote content delivery using your network or you can choose to utilise LAN control.

TECHNICAL CHARACTERISTICS

Brand : IIYAMA
Part number : LH5541UHS-B2
Connectivité :
RS-232C : Yes
Représentation / réalisation :
HDCP : Yes
Certificat :
Certification : CB, CE, TÜV-Bauart, EAC, ErP, WEEE, REACH
AC input frequency : 50 - 60 Hz
AC input voltage : 100 - 240 V
Active display area (W x H) : 1209.6 x 680.4 mm
Batteries included : Yes
Bezel width (bottom) : 1.55 cm
Bezel width (side) : 1.55 cm
Bezel width (top) : 1.55 cm
Built-in processor : Yes
Built-in speaker(s) : Yes

Cables included : AC, HDMI, RS-232
Computer system : Yes
Contrast ratio (typical) : 1200:1
Depth : 69.5 mm
Display brightness : 500 cd/m²
Display depth : 55 mm
Display diagonal : 138.7 cm (54.6»)»
Display diagonal (metric) : 139 cm
Display height : 710 mm
Display number of colours : 1.073 billion colours
Display resolution : 3840 x 2160 pixels
Display technology : LCD
Display weight : 14.3 kg
Display width : 1237 mm
DVI port : Yes
Energy consumption (SDR) per 1000 hours : 444 kWh
Energy efficiency class (SDR) : G
Energy efficiency scale : A to G
Ethernet LAN : Yes
Ethernet LAN (RJ-45) ports : 1
Harmonized System (HS) code : 85285210
Haze rate : 1%
HD type : 4K Ultra HD
HDCP version : 2.2
HDMI ports quantity : 3
Height : 1100 mm
Horizontal scan range : 30 - 80 kHz
Housing material : Metal
Internal memory : 2 GB
Internal storage capacity : 16 GB
Mean time between failures (MTBF) : 50000 h
Native aspect ratio : 16:9
Number of built-in speakers : 2
Number of OSD languages : 11
On Screen Display (OSD) : Yes
On Screen Display (OSD) languages : Czech, German, Dutch, English, Spanish, French, Italian, Japanese, Polish, Russian
Operating hours (hours/days) : 18/7
Operating temperature (T-T) : 0 - 40 °C
Orientation : Horizontal/Vertical
Package depth : 845 mm
Package height : 130 mm
Package width : 1386 mm
Panel mounting interface : 400 x 400 mm
Panel type : IPS
PC Audio in : Yes
Pixel pitch : 0.3155 x 0.3155 mm
Placement supported : Indoor
Power consumption (off) : 0.3 W
Power consumption (standby) : 0.5 W
Power consumption (typical) : 139 W
Processor model : V810
Product colour : Black
Product design : Kiosk design

Purpose : Universal
Quick start guide : Yes
Remote (IR) input : 1
Remote (IR) output : 1
Remote control included : Yes
Response time : 8 ms
RMS rated power : 10 W
Storage temperature (T-T) : -20 - 60 °C
Sustainability certificates : RoHS
Touchscreen : No
VESA mounting : Yes
VGA (D-Sub) input ports : 1
Viewing angle, horizontal : 178°
Viewing angle, vertical : 178°
Weight : 63.8 kg
Width : 1929 mm
Wi-Fi : No