

Tp-link archer MR400 4G lte modem wireless AC1200



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : TP-LINK

Part number : ARCHER MR600

Sécurité :

Stateful Packet Inspection (SPI) : Y

Réseau :

Dynamic DNS (DDNS) : Y

Connexion WAN :

Ethernet WAN : Y

3G standards : HSPA, HSPA+, UMTS

3G/4G USB modem compatibility : Y

4G bands supported : 700,800,850,900,1800,2100,2300,2500,2600 MHz

4G standard : LTE

AC adapter included : Y

AC input frequency : 50/60 Hz

AC input voltage : 110 - 240 V

Antenna design : External

Antennas quantity : 2

Cables included : LAN (RJ-45)

DC-in jack : Y

Depth : 160 mm

Detachable antenna(s) : Y

DHCP client : Y

DHCP server : Y

DMZ support : Y

DoS attack prevention : Y

Dual SIM support : N

Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 4
Ethernet LAN data rates : 10,100,1000 Mbit/s
Ethernet LAN interface type : Gigabit Ethernet
Filtering : Y
Firewall : Y
Firewall security : Domain Filter, IP, MAC Address Binding
Guest access : Y
Height : 37 mm
LED indicators : LAN, Power, WLAN
Linux operating systems supported : Y
Mac operating systems supported : Y
Memory card slot(s) : Y
Mobile network generation : 4G
Networking standards : IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Number of guest networks (2.4 GHz) : 1
Number of guest networks (5 GHz) : 1
Number of products included : 1 pc(s)
Operating relative humidity (H-H) : 10 - 90%
Operating temperature (T-T) : 0 - 40 °C
Output current : 1.5 A
Output voltage : 12 V
Package depth : 223 mm
Package height : 70 mm
Package type : Box
Package width : 307 mm
Parental control : Y
Power source type : AC, DC
Product colour : Black
Product type : Tabletop router
Quality of Service (QoS) support : N
Quick installation guide : Y
Receiver sensitivity : 5 GHz: 11a 54M: -74 dBm 11ac HT20: -66 dBm 11ac HT40: -63 dBm 11ac HT80 : -59 dBm 11n HT20: -73 dBm 11n HT40: -70 dBm 2.4 GHz: 11g 54M: -74 dBm 11n HT20: -72 dBm 11n HT40: -69 dBm
Reset button : Y
Routing protocols : IP
Security algorithms : 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK
SIM card slot : Y
SIM card type : MicroSIM
Storage relative humidity (H-H) : 5 - 90%
Storage temperature (T-T) : -40 - 70 °C
Supported network protocols : IPv4, IPv6
Top Wi-Fi standard : Wi-Fi 5 (802.11ac)
UMTS bands supported : 850,900,2100 MHz
Universal Plug and Play (UPnP) : Y
URL filtering : Y
USB port : N
VPN support : PPTP VPN, IPSec VPN, OpenVPN
WAN connection type : RJ-45
Width : 229 mm
Wi-Fi band : Dual-band (2.4 GHz / 5 GHz)
Wi-Fi Multimedia (WMM)/(WME) : Y
Wi-Fi standards : 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
Windows operating systems supported : Windows 10, Windows 2000, Windows 7, Windows 8, Windows 8.1, Windows 98SE, Windows NT, Windows Vista, Win-

dows XP, Y

WLAN data transfer rate (first band) : 867 Mbit/s

WLAN data transfer rate (max) : 867 Mbit/s

WLAN data transfer rate (second band) : 300 Mbit/s

WPS push button : Y