

# EPDU MI OU (309 32A 3P)30xC13:12xC19



## DESCRIPTION

ePDU G3 Metered Input models allow metering to the branch and phase level for effective load balancing, with no switching. Models include IEC Class 1 ( $\pm 1\%$ ) billing grade accuracy, an advanced hot-swap meter with LCD pixel display showing V, W, A and kWh, and the ability to daisy chain 8 ePDUs to share the same network connection and IP address.

## TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : EMIB34

### Design :

Type : Three-phase

AC input frequency : 50 Hz

AC outlet types : C13 coupler, C19 coupler

AC outlets quantity : 42 AC outlet(s)

Cable colour : Black

Cable length : 3 m

Cables included : LAN (RJ-45)

Depth : 52 mm

Dimensions (WxDxH) : 1829 x 52 x 65 mm

Display : LCD

Ethernet LAN (RJ-45) ports : 1

Firmware upgradeable : Y

Firmware upgradeable via : Network, USB

Form factor : Rackmount

Height : 65 mm

LED indicators : Y

Management protocols : SNMP, Telnet

Maximum current : 32 A

Maximum input current per phase : 32 A

Maximum power : 22000 W

Mounting : Vertical

Nominal input voltage : 400 V

Nominal output voltage : 230 V  
Operating temperature (T-T) : 0 - 60 °C  
Output connections : 30 x C13 & 12 x C19  
Package weight : 6.4 kg  
PDU types : Metered  
Power plug : IEC 60309  
Product colour : Black  
Rack capacity : 0U  
Rack mount kit : Y  
Rack mounting : Y  
Sustainability certificates : RoHS  
Weight : 4.1 kg  
Width : 1829 mm