

16-Port 0U PDU, Met. by Bank /Sw by Out 14 x C13 & 2 x C19



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : ATEN

Part number : PE6216G-AX-G

Caractéristiques :

Certification : CE, C-Tick TUV-CB, GOST

AC input frequency : 50-60 Hz

AC outlet types : C13 coupler, C19 coupler

AC outlets quantity : 16 AC outlet(s)

Cable length : 3 m

Cables included : AC

Depth : 66 mm

Ethernet LAN (RJ-45) ports : 1

Height : 44 mm

LED indicators : Y

Load capacity : 3680 VA

Manual : Y

Master (outer) case gross weight : 6.02 kg

Master (outer) case height : 179 mm

Master (outer) case length : 1415 mm

Master (outer) case net weight : 4.27 kg

Master (outer) case width : 187 mm

Maximum current : 16 A

Monitoring : Current, Voltage

Nominal input voltage : 100-240 V

Operating relative humidity (H-H) : 0 - 80%

Operating temperature (T-T) : 0 - 40 °C

Package depth : 1415 mm

Package height : 179 mm

Package weight : 6 kg
Package width : 187 mm
PDU types : Metered, Switched
Power plug : C20 coupler
Power protection features : Overload
Product colour : Black
Products per master (outer) case : 1 pc(s)
Rack capacity : 0U
Rack mount kit : Y
Security algorithms : SNMP, SNMPv2, SNMPv3
Storage relative humidity (H-H) : 0 - 80%
Storage temperature (T-T) : -20 - 60 °C
Supported network protocols : TCP/IP, UDP, HTTP, HTTPS, SSL, SMTP, DHCP, NTP, DNS, Ping, Telnet
Weight : 4.27 kg
Width : 1324.8 mm