

INFOSEC UPS E4 LCD Pro 20 KVA Tri-Mono



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : INFOSEC
Part number : 67517
Certificat :
Certification : CE
AC outlet types : Terminal
Audible alarm modes : Alarm when on battery, Fault, Overload alarm, Low battery alarm
Audible alarm(s) : Yes
Battery capacity : 9 Ah
Battery recharge time : 9 h
Battery technology : Sealed Lead Acid (VRLA)
Battery voltage : 12 V
Cables included : RS-232, USB cable
Charging current : 4 A
Cold start : Yes
Compliance certificates : RoHS
Crest factor : 3:1
Depth : 815 mm
Display type : LCD
Emergency Power Off (EPO) : Yes
Emergency Power Off (EPO) connector : Yes
Form factor : Tower
Height : 826 mm
Input frequency : 46/64 Hz
Input operation voltage (max) : 520 V
Input operation voltage (min) : 190 V
Input power factor : 0.8
Manual : Yes

Noise level : 60 dB
Number of input phases : 3
Number of output phases : 1
Operating altitude : 0 - 1000 m
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : 0 - 40 °C
Output frequency : 46/64 Hz
Output operation voltage (max) : 240 V
Output operation voltage (min) : 208 V
Output power : 16000 W
Output power capacity : 20 kVA
Output voltage regulation : -1 - 1%
Output voltage Total Harmonic Distortion (THD) : 6%
Package weight : 160 kg
Power factor : 0.8
Product colour : Black
Response time : 0 ms
Serial interface : Yes
Serial interface type : RS-232
Typical backup time at half load : 12 min
UPS topology : Double-conversion (Online)
USB 2:0 ports quantity : 1
USB port : Yes
USB port type : USB Type-B
Waveform : Pure sine
Weight : 145 kg
Width : 250 mm