

HANWHA- 2 Mps Network Dome Camera XND-6081VZ



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : XND-6081V
Représentation / réalisation :
Type : IP security camera
Réseau :
Bluetooth : N
Active tampering alarm : Y
Alarm input/output : Y
Alert notification type : E-mail
Angle of rotation : 355°
Audio formats supported : ADPCM, G.711, G.726, LC-AAC
Back Light Compensation (BLC) : Y
Bit rate control : Constant Bit Rate (CBR)/Variable Bit Rate (VBR), Variable Bit Rate (VBR)
Built-in HDD : N
Built-in microphone : Y
Camera pan control : Y
Camera shutter type : Electronic
Camera tilt control : Y
Card reader integrated : Y
Closest focusing distance : 0.5 m
Compatible memory cards : MicroSD (TransFlash), MicroSDHC, MicroSDXC
Composite video out : 1
Connectivity technology : Wired
Day/night mode : Y
DC-in jack : Y
Diameter : 16 cm
Ethernet interface type : Fast Ethernet

Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Flash memory : 256 MB
Flip & mirror : Y
Focal length range : 2.8 - 12 mm
Focus : Motorized
Form factor : Dome
Frame rate : 60 fps
Height : 125 mm
Highlight Compensation (HLC) : Y
Housing material : Aluminium
IK code : IK10
Image stabilizer : Y
Intelligent Video Surveillance (IVS) system features : Defocus, Face detection, Missing object, People counting
Internal memory : 1024 MB
International Protection (IP) code : IP52
IP address filtering : Y
Languages support : Simplified Chinese, Czech, German, Dutch, English, Spanish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish
Lens viewing angle, diagonal : 142.1°
Lens viewing angle, horizontal : 119.5°
Lens viewing angle, vertical : 62.8°
Mac operating systems supported : Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra
Maximum aperture number : 3.6
Maximum memory card size : 512 GB
Maximum resolution : 1920 x 1080 pixels
Minimum aperture number : 1.4
Minimum illumination : 0.0015 lx
Mounting type : Ceiling
Night vision : N
Noise reduction : Y
Number of cameras : 1
Number of effective pixels (H x V) : 1945 x 1097 pixels
Number of languages : 17
Number of users : 20 user(s)
Operating relative humidity (H-H) : 0 - 90%
Operating temperature (T-T) : -25 - 60 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Pan range : 0 - 360°
Password protection : Y
Password protection type : User
Placement supported : Indoor
Power consumption (max) : 5.4 W
Power consumption (Power over Ethernet (PoE)) : 4.2 W
Power consumption (typical) : 3.1 W
Power source type : DC, PoE
Privacy masking : Y
Product colour : White
PTZ control : Y
PTZ modes : Digital PTZ
Quality of Service (QoS) support : Y
Security algorithms : HTTPS, SSL/TLS
Sensor type : CMOS

Storage relative humidity (H-H) : 0 - 90%
Storage temperature (T-T) : -60 - 60 °C
Streaming method : Multicast, Unicast
Supported graphics resolutions : 320 x 240, 640 x 360, 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 960, 1920 x 1080 (HD 1080)
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour, LLDP, SRTP
Tilt angle range : -45 - 85°
Total megapixels : 2 MP
USB port : Y
Video compression formats : H.264, H.265, M-JPEG
Video formats supported : H.264, H.265, M-JPEG
Video motion detection : Y
Video streaming : Y
Web-based management : Y
Weight : 1.45 kg
White balance : ATW, AWC, Indoor, Manual, Outdoor
Wide Dynamic Range (WDR) : Y
Wi-Fi : N
Windows operating s