



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : RARITAN

Part number : PX3-3211

Caractéristiques :

Certification : CE, Canada ICES-003, Part 15 Class A of the FCC

AC input frequency : 50/60 Hz

AC outlet types : C19 coupler

AC outlets quantity : 2 AC outlet(s)

Cable length : 3 m

Daisy chain : Y

Depth : 183 mm

Display : LCD

Ethernet LAN (RJ-45) ports : 1

Height : 44 mm

LED indicators : Y

Management protocols : HTTP(s); SSH; Telnet; RS-232 (Serial); Power IQ; SNMP version v2/v3; SMTP; JSON-RPC; Modbus over TCP

Maximum current : 16 A

Monitoring : Humidity, Temperature

Nominal input voltage : 100-240 V

Non-operating altitude : 0 - 3048 m

Operating altitude : 0 - 3048 m

Output voltage : 100-240 V

Package depth : 415 mm

Package height : 320 mm

Package weight : 5.05 kg

Package width : 570 mm

PDU types : Managed, Metered, Monitored

Power plug : IEC 320

Product colour : Black

Reset button : Y

Serial ports quantity : 1

Storage relative humidity (H-H) : 0 - 100%

Storage temperature (T-T) : -25 - 65 °C

Sustainability certificates : RoHS

USB ports quantity : 3

Weight : 3.2 kg

Width : 440 mm