

EPDU MI 0U (309 32A 3P)24XC13:6XC19



DESCRIPTION

ePDU G3 Metered Input models allow metering to the branch and phase level for effective load balancing, with no switching. Models include IEC Class 1 ($\pm 1\%$) billing grade accuracy, an advanced hot-swap meter with LCD pixel display showing V, W, A and kWh, and the ability to daisy chain 8 ePDUs to share the same network connection and IP address.

TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : EMIB32

Design :

Type : Three-phase

Caractéristiques :

Certification : CB, CE, EN 60950-1:2006/A11:2009/A1:2010/A12:2011\nIEC 60950-1, EN 61000-6-2:2005\nEN 61000-6-4:2007+A1:2011\nEN 50581 : 2012, REACH, WEEE\nISO 9001:2008 / ISO 14001:2004

AC input frequency : 50 Hz

AC outlet types : C13 coupler, C19 coupler

AC outlets quantity : 30 AC outlet(s)

Cable colour : Black

Cable length : 3 m

Cables included : LAN (RJ-45)

Depth : 53 mm

Dimensions (WxDxH) : 52 x 53 x 1604 mm

Display : LCD

Ethernet LAN (RJ-45) ports : 1

Firmware upgradeable : Y

Firmware upgradeable via : Network, USB

Form factor : Rackmount

Height : 1604 mm

LED indicators : Y

Management protocols : SNMP, Telnet

Maximum current : 32 A

Maximum input current per phase : 32 A

Maximum power : 22000 W
Monitoring : Voltage
Mounting : Vertical
Nominal input voltage : 400 V
Nominal output voltage : 230 V
Operating temperature (T-T) : 0 - 60 °C
Output connections : 24 x C13 & 6 x C19
Package depth : 214 mm
Package height : 1730 mm
Package width : 200 mm
PDU types : Metered
Power plug : IEC 60309
Product colour : Black
Rack capacity : 0U
Rack mount kit : Y
Rack mounting : Y
Serial ports quantity : 1
Supported network protocols : HTTP, HTTPS, SSL, FTP, SMTP, DNS, DHCP, LDAP, RADIUS
Sustainability certificates : RoHS
Weight : 6 kg
Width : 52 mm