

Eaton 9SX 6000i



DESCRIPTION

The Eaton 9SX UPS offers high availability, flexibility and advanced protection for infrastructure, industrial, medical, IT, networking, storage and telecom. Delivering on-line double conversion protection in versatile Rack/Tower format with up to 95% efficiency.

TECHNICAL CHARACTERISTICS

Brand : EATON
Part number : 9SX6KI
AC outlet types : Terminal
Automatic battery test : Y
Crest factor : 3:1
Depth : 244 mm
Display type : LCD
Efficiency : 98%
Form factor : Tower
Height : 542 mm
Input current Total Harmonic Distortion (THD) : 5%
Input frequency : 40/70 Hz
Input operation voltage (max) : 276 V
Input operation voltage (min) : 120 V
Maximum current : 90 A
Noise level : 46 dB
Operating temperature (T-T) : 0 - 40 °C
Output operation voltage (max) : 240 V
Output operation voltage (min) : 200 V
Output power : 5400 W
Output power capacity : 6 kVA
Output voltage regulation : 1%
Output voltage Total Harmonic Distortion (THD) : 2%
Power plug : Terminal
Product colour : Black
RS-232 ports : 1

Sustainability certificates : ENERGY STAR
Typical backup time at half load : 15 min
UPS topology : Double-conversion (Online)
USB 2:0 ports quantity : 1
Weight : 65.5 kg
Width : 545 mm