

HANWHA- 4K AI Box Camera XNB-9003



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA

Part number : XNB-9003

Représentation / réalisation :

Type : IP security camera

Active tampering alarm : Y

Alarm input channels : 2

Anti-flicker : Y

Audio detection : Y

Audio formats supported : AAC-LC, ADPCM, G.711, G.711 -law, G.726

Audio input channels : 1

Audio output channels : 1 channels

Back Light Compensation (BLC) : Y

Bit rate control : Constant Bit Rate (CBR), Variable Bit Rate (VBR)

Camera shutter speed : 1/12000 s

Camera shutter type : Electronic

Card reader integrated : Y

Compatible memory cards : MicroSD (TransFlash), MicroSDHC, MicroSDXC

Connectivity technology : Wired

Day/night mode : Y

DC output voltage : 12

Depth : 165 mm

Dynamic range : 120 dB

Ethernet interface type : Fast Ethernet

Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 1

Flash memory : 512 MB

Flip & mirror : Y

| |
|---|
| Form factor : Box |
| Frame rate : 120 fps |
| Height : 67 mm |
| Housing material : Aluminium |
| HTTPS encryption : Y |
| Image stabilizer : Y |
| Infrared (IR) cut-off filter : Y |
| IP address filtering : Y |
| Languages support : Simplified Chinese, Czech, German, Dutch, English, Spanish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish |
| Maximum memory card size : 512 GB |
| Maximum resolution : 3840 x 2160 pixels |
| Minimum illumination : 0.03 lx |
| Mounting type : Ceiling/wall |
| Night vision : Y |
| Noise reduction : Y |
| Number of cameras : 1 |
| Number of languages : 17 |
| Number of sensors : 1 |
| Number of users : 20 user(s) |
| Operating relative humidity (H-H) : 0 - 95% |
| Operating temperature (T-T) : -10 - 55 °C |
| Optical sensor size : 25.4 / 1.8 mm (1 / 1.8») |
| People counting function : Y |
| Placement supported : Indoor & outdoor |
| Power consumption (max) : 19 W |
| Power consumption (Power over Ethernet (PoE)) : 12.9 W |
| Power consumption (typical) : 9.5 W |
| Power source type : DC, PoE |
| Privacy masking : Y |
| Product colour : Black |
| PTZ control : Y |
| PTZ modes : Digital PTZ, Preset point |
| Quality of Service (QoS) support : Y |
| RS-485 ports : 1 |
| Sensor type : CMOS |
| Storage relative humidity (H-H) : 0 - 90% |
| Storage temperature (T-T) : -50 - 60 °C |
| Streaming method : Multicast, Unicast |
| Supported graphics resolutions : 320 x 240, 640 x 360, 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2592 x 1944, 2688 x 1520, 3072 x 1728, 3840 x 2160 |
| Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP (TCP, UDP Unicast |
| USB port : Y |
| Video compression formats : H.264, H.265, M-JPEG |
| Video formats supported : H.264, H.265, M-JPEG |
| Video intelligence analytic : Y |
| Video motion detection : Y |
| Video streaming : Y |
| Web browser : Y |
| Weight : 880 g |
| White balance : ATW, AWC, Indoor, Manual, Outdoor |
| Wide Dynamic Range (WDR) : Y |

Width : 81 mm