

16-Port 0U PDU Met. & Sw by Out 14 x C13 & 2 x C19

16Amp



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : ATEN	
Part number : PE8216G-AX-G	
Caractéristiques :	
Certification :	TUV-CB, CE-LVD, CE
AC input frequency :	50/60 Hz
AC outlet types :	C13 coupler, C19 coupler
AC outlets quantity :	16 AC outlet(s)
Cable length :	1.6 m
Depth :	1324.8 mm
Height :	44 mm
Housing material :	Metal
LED indicators :	Y
Load capacity :	3680 VA
Management platform :	SNMP v1/v2/v3
Master (outer) case gross weight :	6.21 kg
Master (outer) case height :	179 mm
Master (outer) case length :	1415 mm
Master (outer) case net weight :	4.47 kg
Master (outer) case width :	187 mm
Maximum current :	16 A
Nominal input voltage :	100 - 240 V
Nominal output voltage :	100 - 240 V
Operating relative humidity (H-H) :	0 - 80%
Operating temperature (T-T) :	0 - 40 °C
Package depth :	1415 mm
Package height :	179 mm
Package weight :	6.22 kg

Package width : 187 mm
PDU types : Metered, Switched
Power plug : C20 coupler
Product colour : Black
Products per master (outer) case : 1 pc(s)
Storage temperature (T-T) : -20 - 60 °C
Weight : 4.47 kg
Width : 66 mm