

HANWHA- 6 Mps AI Box Camera XNB-8003



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : XNB-8003
Représentation / réalisation :
Type : IP security camera
Active tampering alarm : Y
Alarm input channels : 2
Anti-flicker : Y
Audio detection : Y
Audio formats supported : AAC-LC, ADPCM, G.711, G.711 -law, G.726
Audio input channels : 1
Audio output channels : 1 channels
Back Light Compensation (BLC) : N
Bit rate control : Constant Bit Rate (CBR), Variable Bit Rate (VBR)
BNC output ports : 1
Camera shutter speed : 1/12000 s
Camera shutter type : Electronic
Card reader integrated : Y
Compatible memory cards : MicroSD (TransFlash), MicroSDHC, MicroSDXC
Connectivity technology : Wired
Day/night mode : Y
DC output voltage : 12
Depth : 165 mm
Dynamic range : 120 dB
Ethernet interface type : Fast Ethernet
Ethernet LAN : Y
Flash memory : 512 MB
Flip & mirror : Y

Form factor : Box
Frame rate : 120 fps
Height : 67 mm
Housing material : Aluminium
Image stabilizer : Y
Infrared (IR) cut-off filter : Y
IP address filtering : Y
Languages support : Simplified Chinese, Czech, German, Dutch, English, Spanish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish
Maximum memory card size : 512 GB
Maximum resolution : 3328 x 1872 pixels
Minimum illumination : 0.03 lx
Mounting type : Ceiling/wall
Night vision : Y
Noise reduction : Y
Number of cameras : 1
Number of languages : 17
Number of sensors : 1
Number of users : 20 user(s)
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : -10 - 55 °C
Optical sensor size : 25.4 / 1.8 mm (1 / 1.8»)
People counting function : Y
Placement supported : Indoor & outdoor
Power consumption (max) : 19 W
Power consumption (Power over Ethernet (PoE)) : 12.9 W
Power consumption (typical) : 9.5 W
Power source type : DC, PoE
Privacy masking : Y
Product colour : Black
PTZ control : Y
PTZ modes : Digital PTZ, Preset point
Quality of Service (QoS) support : Y
RS-422 ports : 1
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 90%
Storage temperature (T-T) : -50 - 60 °C
Streaming method : Multicast, Unicast
Supported graphics resolutions : 320 x 240, 640 x 360, 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2592 x 1944, 2688 x 1520, 3072 x 1728
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP (TCP, UDP Unicast)
Total megapixels : 6 MP
USB port : Y
Video formats supported : H.264, H.265, M-JPEG
Video motion detection : Y
Video streaming : Y
Web browser : Y
Weight : 880 g
White balance : ATW, AWC, Indoor, Manual, Outdoor
Wide Dynamic Range (WDR) : Y
Width : 81 mm