

HANWHA- Camera 4K PNV-A9081RLP



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA

Part number : PNV-A9081RLP

Représentation / réalisation :

Type : IP security camera

Alert notification type : E-mail

Camera shutter speed : 1/5~1/12000 s

Camera shutter type : Electronic

Connectivity technology : Wired

Day/night mode : Y

DC output voltage : 12

Detect distance (tele) : 183 m

Detect distance (wide) : 62.9 m

Diameter : 18 cm

Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 1

Flash memory : 512 MB

Form factor : Dome

Height : 125 mm

Housing material : Aluminium

HTTPS encryption : Y

Identify distance (tele) : 18.3 m

Identify distance (wide) : 6.3 m

IK code : IK10+

Internal memory : 4096 MB

International Protection (IP) code : IP66, IP67, IP69K

IP address filtering : Y

Languages support : Simplified Chinese, Czech, German, Dutch, English, Spanish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Rus-

sian, Swedish, Turkish

Maximum aperture number : 2.65

Maximum resolution : 3840 x 2160 pixels

Minimum aperture number : 1.6

Mounting type : Ceiling

Number of cameras : 1

Number of languages : 17

Number of lenses : 1

Observe distance (tele) : 73.3 m

Observe distance (wide) : 25.1 m

Operating relative humidity (H-H) : 0 - 90%

Operating temperature (T-T) : -40 - 55 °C

Optical sensor size : 25.4 / 1.8 mm (1 / 1.8»)

Pan range : 0 - 360°

Placement supported : Outdoor

Power consumption (Power over Ethernet (PoE)) : 20 W

Power source type : DC, PoE

Product colour : White

Recognize distance (tele) : 36.6 m

Recognize distance (wide) : 12.6 m

Security algorithms : EAP-LEAP, EAP-TLS, HTTPS, SSL/TLS

Sensor type : CMOS

Storage relative humidity (H-H) : 0 - 90%

Storage temperature (T-T) : -50 - 60 °C

Streaming method : Multicast, Unicast

Supported graphics resolutions : 640 x 360, 720 x 576, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 960, 1600 x 1200 (UXGA), 1920 x 1080 (HD 1080), 2048 x 1536 (QXGA), 2560 x 1440, 3072 x 1728, 3840 x 2160

Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP (TCP, UDP Unicast)

Tilt angle range : -45 - 85°

User access level : User

Video intelligence analytic : Y

Weight : 1.9 kg

White balance : ATW, AWC, Indoor, Manual, Outdoor