

Eaton FlexPDU 6 BS



DESCRIPTION

Eaton Flex Rack PDU

TECHNICAL CHARACTERISTICS

Brand : EATON
Part number : EFLX6B
Caractéristiques :
Certification : CB, CE, EN 60950-1:2006/A11:2009/A1:2010/A12:2011 Safety - Part 1: General Requirements, IEC 60950-1(ed.2), IEC 60950-1(ed.2);am1 EN 55022:2010, EN 61000-6-2:2005 Part 6-2, EN 50581 : 2012, REACH, WEEE, PEP, ISO 9001:2008, ISO
AC input frequency : 50 - 60 Hz
AC outlets quantity : 6 AC outlet(s)
Cable length : 2 m
Dimensions (WxDxH) : 120 x 52 x 483 mm
Maximum current : 16 A
Monitoring : Current
Mounting : Horizontal/Vertical
Nominal input voltage : 230 V
Operating temperature (T-T) : 0 - 60 °C
PDU types : Monitored
Product colour : Black
Rack capacity : 1U
Supported network protocols : HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS
Sustainability certificates : RoHS
Weight : 1.6 kg