

HANWHA- Camera LNV-6022R



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA

Part number : LNV-6022R

Représentation / réalisation :

Type : IP security camera

Active tampering alarm : Y

Alert notification type : E-mail

Angle of rotation : 355°

Anti-flicker : Y

Back Light Compensation (BLC) : Y

Bit rate control : Constant Bit Rate (CBR), Variable Bit Rate (VBR)

Camera pan control : Y

Camera shutter type : Electronic

Camera tilt control : Y

Card reader integrated : Y

Closest focusing distance : 0.5 m

Compatible memory cards : MicroSD (TransFlash), MicroSDHC

Connectivity technology : Wired

Day/night mode : Y

Diameter : 12 cm

Dynamic range : 120 dB

Ethernet interface type : Fast Ethernet

Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 1

Fixed focal length : 4 mm

Fixed focus : Y

Flash memory : 256 MB

Flip & mirror : Y

| |
|--|
| Form factor : Dome |
| Frame rate : 30 fps |
| Height : 91.7 mm |
| Housing material : Plastic |
| HTTPS encryption : Y |
| Identify distance : 0.5 m |
| IK code : IK10 |
| Infrared (IR) cut-off filter : Y |
| Internal memory : 512 MB |
| International Protection (IP) code : IP66 |
| IP address filtering : Y |
| Languages support : Simplified Chinese, Czech, German, Dutch, English, Spanish, French, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish |
| LED type : IR |
| Lens viewing angle, diagonal : 98.3° |
| Lens viewing angle, horizontal : 84.3° |
| Lens viewing angle, vertical : 45.6° |
| Mac operating systems supported : Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave |
| Maximum aperture number : 2 |
| Maximum memory card size : 32 GB |
| Maximum resolution : 1920 x 1080 pixels |
| Minimum illumination : 0.03 lx |
| Mirror : Y |
| Mounting type : Ceiling |
| Networking standards : IEEE 802.3af |
| Night vision : Y |
| Night vision distance : 30 m |
| Noise reduction : Y |
| Number of cameras : 1 |
| Number of effective pixels (H x V) : 1984 x 1105 pixels |
| Number of languages : 15 |
| Number of lenses : 1 |
| Number of sensors : 1 |
| Number of users : 6 user(s) |
| Operating relative humidity (H-H) : 0 - 90% |
| Operating temperature (T-T) : -30 - 55 °C |
| Optical sensor size : 25.4 / 2.8 mm (1 / 2.8») |
| Pan range : 0 - 350° |
| Placement supported : Indoor & outdoor |
| Power consumption (Power over Ethernet (PoE)) : 6.4 W |
| Power consumption (typical) : 5 W |
| Power source type : PoE |
| Privacy masking : Y |
| Product colour : White |
| Progressive scan : Y |
| Protection features : Dust resistant, Splash proof |
| PTZ control : N |
| Quality of Service (QoS) support : Y |
| Remote viewing : Y |
| Security algorithms : 802.1x RADIUS, EAP-LEAP, EAP-TLS, HTTPS |
| Sensor type : CMOS |
| Storage relative humidity (H-H) : 0 - 90% |
| Storage temperature (T-T) : -30 - 55 °C |
| Streaming method : Multicast, Unicast |

| |
|--|
| Supported graphics resolutions : 320 x 240, 640 x 360, 640 x 480 (VGA), 720 x 576, 800 x 448, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080) |
| Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour |
| Tilt angle range : 0 - 67° |
| Total megapixels : 2 MP |
| Video compression formats : H.264, M-JPEG |
| Video formats supported : H.264, M-JPEG |
| Video motion detection : Y |
| Video streaming : Y |
| Web browser : Y |
| Weight : 410 g |
| White balance : ATW, AWC, Indoor, Manual, Outdoor |
| Wide Dynamic Range (WDR) : Y |
| Width : 120.3 mm |
| Windows operating systems supported : Windows 10, Windows 7, Windows 8.1 Enterprise |
| Zoom capability : Y |