



DESCRIPTION

ATEN PSS PP v3.0 Secure KVM Switch (CS1182DP) is specifically designed to meet the stringent security requirement of secure defense and intelligence installations. ATEN PSS PP v3.0 Secure KVM Switch (CS1182DP) is compliant with PSS PP v3.0 (Protection Profile for Peripheral Sharing Switch, Version 3.0) standard certified by the National Information Assurance Partnership (NIAP).

- 1x CS1182DP 2-Port USB DisplayPort Secure KVM Switch
- 1x LIN2-418K-E12G Power Cord
- 1x User Instructions

TECHNICAL CHARACTERISTICS

Brand : ATEN
Part number : CS1182DP-AT-G
AC input frequency : 50/60 Hz
AC input voltage : 100 - 240 V
Audio connections : Y
Built-in display : N
Cables included : AC
Console ports : 3.5mm headphone, HDMI, PS/2, USB A
Console USB ports quantity : 2
Depth : 163 mm
DisplayPorts quantity : 2
Harmonized System (HS) code : 85176200
HD type : 4K Ultra HD
HDMI ports quantity : 1
Headphone outputs : 3
Height : 44 mm
Housing material : Metal
Input current : 1 A
Keyboard port type : USB
LED indicators : Y
Manual : Y
Master (outer) case gross weight : 8.35 kg

Master (outer) case height : 258 mm
Master (outer) case length : 565 mm
Master (outer) case net weight : 5.82 kg
Master (outer) case width : 375 mm
Maximum resolution : 3840 x 2160 pixels
Mouse port type : USB
Number of computers controlled : 2
Operating relative humidity (H-H) : 0 - 80%
Operating temperature (T-T) : 0 - 50 °C
Package depth : 540 mm
Package height : 233 mm
Package weight : 2.47 kg
Package width : 116 mm
Power consumption (typical) : 3.8 W
Power source : AC
Product colour : Black
Products per master (outer) case : 3 pc(s)
Push button : Y
Quick installation guide : Y
Rack capacity : 1U
Rack mounting : Y
Storage temperature (T-T) : -20 - 60 °C
Sustainability certificates : RoHS
USB 2:0 Type-B ports quantity : 4
USB connector type : USB Type-B
Video bandwidth : 30 Hz
Video port type : DisplayPort
Weight : 1.94 kg
Width : 335 mm
Windows operating systems supported : Y