

LEGRAND UPS Keor DC 25 VA



DESCRIPTION

Keor DC is the new UPS designed to provide the continuity of operation in case of power failure to all Internet connected devices such as modem, router, cordless or VoIP phones.

Its elegant and modern design, with ultra-compact dimensions, allows it to adapt perfectly to the home, even in small spaces.

Keor DC is powered via the 230 Va.c. home network and can power most routers and phones on the market as it is equipped with 4 different power jacks.

TECHNICAL CHARACTERISTICS

Brand : LEGRAND

Part number : 311010

Design :

Certification : EN55032, IEC/EN 62368-1

Auto shut-off : N

Battery capacity : 2.2 Ah

Battery recharge time : 3 h

Battery technology : Lithium-Ion (Li-Ion)

Battery voltage : 3.7 V

Depth : 28 mm

Efficiency : 98%

Form factor : Compact

Harmonized System (HS) code : 85078000

Height : 95 mm

Input frequency : 47/63 Hz

Input operation voltage (max) : 264 V

Input operation voltage (min) : 90 V

LED indicators : Y

Master (outer) case gross weight : 9.84 kg

Master (outer) case height : 238 mm

Master (outer) case length : 506 mm

Master (outer) case width : 406 mm

Maximum current : 2 A
Number of input phases : 1
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : 0 - 35 °C
Output frequency : 50/60 Hz
Output operation voltage (max) : 19 V
Output operation voltage (min) : 9 V
Output power : 25 W
Package depth : 0.25 mm
Package height : 95 mm
Package weight : 585.2 g
Package width : 95 mm
Pallet net height : 110.2 cm
Pallet net length : 100 cm
Pallet net weight : 157.4 kg
Pallet net width : 120 cm
Potential-free output : N
Power plug : C14 coupler
Power protection features : Overcharge, Overheating, Short circuit
Power source type : DC
Product colour : Black, White
Products per master (outer) case : 14 pc(s)
Products per pallet : 224 pc(s)
Safety : FCC: Class B, UL/cULus
Weight : 300 g
Width : 95 mm