

Eaton 9SX 2000i Rack2U



DESCRIPTION

The Eaton 9SX UPS offers high availability, flexibility and advanced protection for infrastructure, industrial, medical, IT, networking, storage and telecom. Delivering on-line double conversion protection in versatile Rack/Tower format with up to 95% efficiency.

TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : 9SX2000IR

Design :

Certification : IEC/EN 62040 -2 , FCC B, CISPR22 B, CE /CB report (TUV) / cULus / EAC / RCM / BIS / KCC

AC outlet types : C13 coupler, C14 coupler

AC outlets quantity : 9 AC outlet(s)

Depth : 608 mm

Display type : LCD

Form factor : Rackmount

Height : 86.5 mm

Input frequency : 40 - 70 Hz

Input operation voltage (max) : 276 V

Input operation voltage (min) : 190 V

Maximum current : 10 A

Noise level : 45 dB

Operating temperature (T-T) : 0 - 40 °C

Output frequency : 50/60 Hz

Output power : 1800 W

Output power capacity : 2 kVA

Power plug : C14 coupler

Product colour : Black

Rack capacity : 2U

Safety : IEC/EN 62040-1, UL 1778, CSA 22.2

Serial interface : Y

Serial interface type : RS-232

UPS topology : Double-conversion (Online)

USB 2:0 ports quantity : 1

USB port : Y

Weight : 26.5 kg

Width : 438 mm