

Avigilon camera dome ptz lightcatcher 2.0 mpx



DESCRIPTION

Solidité et précision !

Caractéristiques principales :

- 2 MP
- WDR
- Technologie LightCatcher
- Analyse vidéo par auto-apprentissage
- Objectif : 4.3 à 129 mm
- Zoom x30
- IP66 et IP67
- HDSM Smartcodec

TECHNICAL CHARACTERISTICS

Brand : AVIGILON

Part number : 2.0C-H4PTZ-DP30

Représentation / réalisation :

Type : IP security camera

Réseau :

Bluetooth : N

Vidéo :

Full HD : Y

Plug and Play : Y

3D NR (Noise Reduction) : Y

AC input voltage : 24 V

Active tampering alarm : Y

Adjustment shutter speed : Auto/Manual

Alarm input/output : Y

Analog signal format system : NTSC, PAL

Auto flip : Y

Back Light Compensation (BLC) : Y
Behavior analysis : Intrusion detection, Line crossing detection, Object removal detection, Unattended baggage detection
Bit rate control : Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Built-in HDD : N
Cabling technology : 10/100Base-T(X)
Camera shutter speed : 1/1 - 1/10000 s
Camera shutter type : Electronic
Card reader integrated : Y
Compatible memory cards : SD, SDHC, SDXC
Connectivity technology : Wired
Day/night mode : Y
DC output voltage : 24
Diameter : 23.2 cm
Digital Wide Dynamic Range (DWDR) : Y
Digital zoom : 100x
Ethernet interface type : Fast Ethernet
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Field of view (FOV) angle : 63.7°
Firmware upgradeable : Y
Flip & mirror : Y
Focal length range : 2.3 - 63.7 mm
Fog proof : Y
Form factor : Dome
Frame rate : 60 fps
Headphone outputs : 1
Height : 222.7 mm
Housing material : Aluminium, Nylon
HTTPS encryption : Y
Image quality adjustment : Brightness, Contrast, Saturation, Sharpness
Image stabilizer : Y
Infrared (IR) cut-off filter : Y
Intelligent Video Surveillance (IVS) system features : Abandoned object, Covering detection, Crossing line, Intrusion, Missing object, Scene change
International Protection (IP) code : IP66, IP67
IP address filtering : Y
LED indicators : Link, Status
Maximum aperture number : 4.7
Maximum resolution : 1920 x 1080 pixels
Minimum aperture number : 1.6
Minimum illumination : 0.1 lx
Motion sensor : Y
Mounting type : Wall
Networking standards : IEEE 802.1x
Night vision : Y
Noise reduction : Y
Noise reduction technology : Ultra 3D noise reduction
Number of cameras : 1
Number of effective pixels (H x V) : 1920 x 1080 pixels
Number of lenses : 1
Number of sensors : 1
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : -10 - 50 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)

Optical zoom : 30x
Pan range : 0 - 360°
Pan speed : 450 °/sec
Password protection : Y
Password protection type : User
Placement supported : Outdoor
Power consumption (max) : 23 W
Power consumption (Power over Ethernet (PoE)) : 23 W
Power source type : AC, DC, PoE
Preset points : Y
Privacy masking : Y
Privacy protection : Y
Product colour : Grey, Transparent, White
Progressive scan : Y
PTZ control : Y
PTZ modes : Preset point
Region of Interest (ROI) encoding : Y
Remote viewing : Y
Remotely operated : Y
Sample rate : 8 kHz
Security algorithms : 802.1x RADIUS
Sensor type : WDR
Storage relative humidity (H-H) : 0 - 95%
Storage temperature (T-T) : -10 - 70 °C
Streaming method : Multicast
Supported graphics resolutions : 320 x 256, 1920 x 1080 (HD 1080)
Supported network protocols : IPv6, IPv4, HTTP, HTTPS, SOAP, DNS, NTP, RTSP, RTCP, RTP, TCP,UDP, IGMP, ICMP, DHCP, Zeroconf, ARP, LLDP
Supported video modes : 1080p
Terminal block port : Y
Tilt angle range : -10 - 90°
Tilt speed : 360 °/sec
Total megapixels : 2 MP
Tour recording : Y
Video compression formats : H.264, M-JPEG, MPEG4
Video motion detection : Y
Video streaming : Y
Voice codecs : G.711
&em