



DESCRIPTION

15» Projective Capacitive 10pt touchscreen

The ProLite T1521MSC-B2 15 touchscreen is based on projected capacitive technology, offering optimal seamless and accurate touch response. Due to its glass overlay, it guarantees high durability, scratch-resistance and perfect picture performance. A solid and steady base supports the touchscreen with an adjustable stand offering up to 70 degree tilt angles. Menu buttons are located on the back of the screen which can be locked to prevent tampering, and includes a handy function to deactivate the touchscreen for cleaning. The ProLite T1521MSC-B2 is an incredibly powerful touch solution, perfect for instore retail purposes.

b>TOUCH TECHNOLOGY - CAPACITIVE

This technology uses a sensor-grid of micro-fine wires integrated into the glass that covers the screen. Touch is detected because electrical characteristics of the sensor grid change when human finger is placed on the glass. Thanks to the glass overlay this technology is highly durable, and the touch function remains unaffected even if the glass is scratched. It offers perfect picture performance and will work with human finger (also latex gloved) and stylus-pen.

SCRATCH RESISTANCE

Scratch resistance is essential for touch solutions used in public places and schools. This is achieved thanks to a glass overlay covering the screen. It guarantees high durability of the touch function and even more importantly the touch function remains unaffected even if the glass is scratched.

IP65

The IP code classifies and rates the degree of protection against water intrusion. IP65 means that the monitor is protected to water splashes against the enclosure from any direction.

SPEAKERS

This LED monitor is equipped with two high quality stereo speakers.

VESA

VESA mount compliance means you can easily mount the display to any mounting that complies with the VESA standard.

TECHNICAL CHARACTERISTICS

Brand : IIYAMA

Part number : T1521MSC-B2

Représentation / réalisation :

NVIDIA G-SYNC : No

AMD FreeSync : No

Connectivité :

HDMI : Yes

Écran :

DDC/CI : Yes

AC adapter output voltage : 12 V

Backlight type : LED

Built-in camera : No

Built-in speaker(s) : Yes

Built-in USB hub : No

Cable management : Yes

Cables included : HDMI, Power, USB

Contrast ratio (typical) : 800:1

Depth (with stand) : 198 mm

Display brightness (peak) : 370 cd/m²

Display brightness (typical) : 325 cd/m²

Display diagonal : 38.1 cm (15»)

Display diagonal (metric) : 38 cm

Display number of colours : 16.7 million colours

Display resolution : 1024 x 768 pixels

Display surface : Matt

Display technology : LED

Energy consumption (SDR) per 1000 hours : 11 kWh

Energy efficiency class (SDR) : E

Energy efficiency scale : A to G

European Product Registry for Energy Labelling (EPREL) code : 1385536

Feet colour : Black

Glass thickness : 1.2 mm

HD type : XGA

HDMI ports quantity : 1

Height (with stand) : 308 mm

Horizontal scan range : 31.4 - 60 kHz

International Protection (IP) code : IP65

Manual : Yes

Market positioning : Business

Native aspect ratio : 4:3

Number of OSD languages : 8

Number of simultaneous touchpoints : 10

Number of speakers : 2

On Screen Display (OSD) : Yes

On Screen Display (OSD) languages : German, English, Spanish, French, Italian, Japanese, Russian

Panel mounting interface : 75 x 75 mm

Panel type : TN

Pixel pitch : 0.297 x 0.297 mm

Power adapter included : Yes

Power consumption (off) : 0.5 W

Power consumption (standby) : 1.5 W

Power consumption (typical) : 16 W

Power supply type : External

Product colour : Black

Quick start guide : Yes
Response time : 8 ms
RMS rated power : 4 W
Screen shape : Flat
Stand included : Yes
Surface hardness : 7H
Sustainability certificates : CE, EAC, ErP, REACH, RoHS, UKCA, WEEE, cUL
Sustainability compliance : Yes
Tilt adjustment : Yes
Tilt angle range : 10 - 70°
Touch technology : Multi-touch
Touchscreen : Yes
Touchscreen technology : Projected capacitive system
Touchscreen type : Tabletop
VESA mounting : Yes
VGA (D-Sub) ports quantity : 1
Viewable size, horizontal : 22.8 cm
Viewable size, vertical : 30.4 cm
Viewing angle, horizontal : 170°
Viewing angle, vertical : 160°
Weight (with stand) : 3.5 kg
Width (with stand) : 340 mm