

Ultra short throw benq MW855UST projector



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : BENQ
Part number : 9H.JKS77.24E
Réseau :
Smart TV : N
3D : Y
AC (power) in : Y
AC input frequency : 50 - 60 Hz
AC input voltage : 100 - 240 V
Analog signal format system : NTSC, PAL, SECAM
Aperture range (F-F) : 2.5 - 2.5
Audio (L/R) in : 1
Batteries included : Y
Built-in display : N
Built-in speaker(s) : Y
Cable lock slot : Y
Cable lock slot type : Kensington
Cables included : AC, VGA
Card reader integrated : N
Composite video in : 1
Contrast ratio (typical) : 10000:1
Depth : 373.3 mm
DVI port : N
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Fixed focal length : 2.5 mm
Focus : Manual
Harmonized System (HS) code : 85286200

HDMI connector type : Full-size
HDMI ports quantity : 2
Height : 206.9 mm
Horizontal scan range : 15 - 102 kHz
Keystone correction, horizontal : -15 - 15°
Keystone correction, vertical : -15 - 15°
Lamp power : 240 W
Lamps quantity : 1 lamp(s)
Light source type : Lamp
Manual : Y
Matrix size : 1.65 cm (0.65»)
Matrix type : DMD
Mini-USB 2:0 ports quantity : 1
Native aspect ratio : 16:10
Noise level : 34 dB
Noise level (economic mode) : 29 dB
Number of built-in speakers : 2
Number of colours : 1.073 billion colours
Number of OSD languages : 28
Offset : 122%
On Screen Display (OSD) : Y
On Screen Display (OSD) languages : Arabic, Bulgarian, Simplified Chinese, Traditional Chinese, Croatian, Czech, Danish, German, Dutch, English, Spanish, Finnish, French, Greek, Hindi, Hungarian, Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Romanian, Russian, Swedish, Thai, Turkish
Operating relative humidity (H-H) : 10 - 90%
Operating temperature (T-T) : 0 - 40 °C
PC Audio in : Y
PC Audio out : Y
Placement : Desktop
Power consumption (economy mode) : 260 W
Power consumption (max) : 350 W
Power consumption (standby) : 0.5 W
Power consumption (typical) : 320 W
Power source : AC
Product colour : Black, White
Product type : Ultra short throw projector
Projection technology : DLP
Projector brightness : 3500 ANSI lumens
Projector native resolution : WXGA (1280x800)
Remote control included : Y
RMS rated power : 20 W
Screen size compatibility : 2032 - 2540 mm (80 - 100»)
Serial interface type : RS-232
Service life of light source : 5000 h
Service life of light source (economic mode) : 8000 h
Storage relative humidity (H-H) : 10 - 90%
Storage temperature (T-T) : -20 - 60 °C
Supported graphics resolutions : 640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 832 x 624, 1024 x 768 (XGA), 1152 x 864 (XGA+), 1152 x 870, 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 768 (WXGA), 1280 x 800 (WXGA), 1280 x 960, 1360 x 768 (WXGA), 1400 x 1050 (SXGA+), 1440 x 900 (WXGA+), 1600 x 1200 (UXGA), 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA)
Supported video modes : 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Throw ratio : 0.35
USB 2:0 ports quantity : 1
USB 2:0 Type-B ports quantity : 1

Vertical lens shift range : -2 - 2%
Vertical scan range : 23 - 120 Hz
VGA (D-Sub) ports quantity : 2
Weight : 5 kg
Width : 287.5 mm
Wi-Fi : N
Zoom type : Fixed