

93PS-15(20)-15-2x9Ah-MBS-6



DESCRIPTION

The Eaton 93PS provides the lowest Total Cost of Ownership and maximum availability in its power range. Providing top of the line efficiency and resiliency, its the perfect choice for small data centers and mission critical applications.

TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : BA51AB306A01100000

Design :

Certification : IEC 62040-2 IEC 62040-3

Battery capacity : 9 Ah

Battery technology : Sealed Lead Acid (VRLA)

Battery voltage : 12 V

Depth : 750 mm

Display type : LCD

Efficiency : 96%

Form factor : Tower

Height : 1300 mm

Hot-swap battery : Y

Input frequency : 50/60 Hz

Input operation voltage (max) : 415 V

Input operation voltage (min) : 220 V

International Protection (IP) code : IP20

LED indicators : Y

Number of batteries supported : 64

Number of input phases : 3

Number of output phases : 3

Output frequency : 50/60 Hz

Output operation voltage (max) : 415 V

Output operation voltage (min) : 220 V

Output power : 15000 W

Output power capacity : 15 kVA

Output power factor : 1

Power protection features : Overload

Product colour : Black

Safety : IEC 62040-1

UPS topology : Double-conversion (Online)

Width : 335 mm