

HANWHA- 2 Mps 32x Zoom Network PTZ Camera QNP-6320H



DESCRIPTION

Weight and size reduced up to 55%, better performance, easier installation

New Q series PTZ reduced the weight by up to 55% for the Dome type (QNP-6230RH) and the size became more compact than conventional PTZ cameras. More compact and lighter design significantly reduce the burden of installation. Moreover, the lightened head increased the speed of Pan/Tilt.

Precise PTZ control

New Q series PTZ supports delicate and precise PTZ control. Conventional PTZ cameras had challenges in offering precise monitoring of moving objects due to its pre-set centered movement. New Q series PTZ provides stable object monitoring using precise PTZ control when a user wants to track moving objects manually.

Widened Tilt angle

QNP-6320R/6250R offers 110° (-20° ~ 90°) of Tilt angle, enabling effective monitoring of objects positioned above the camera level and objects in sloped environment.

TECHNICAL CHARACTERISTICS

Brand : HANWHA

Part number : QNP-6320H

Représentation / réalisation :

Type : IP security camera

Alert notification type : E-mail

Compatible memory cards : MicroSD (TransFlash), MicroSDHC, MicroSDXC

Connectivity technology : Wired

Day/night mode : Y

Detect distance (tele) : 1921.3 m

Detect distance (wide) : 64.2 m

Diameter : 20.4 cm

Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 1

Flash memory : 256 MB

Focal length range : 4.44 - 142.6 mm

Form factor : Dome
Height : 265 mm
HTTPS encryption : Y
Identify distance (tele) : 192.1 m
Identify distance (wide) : 6.1 m
IK code : IK10
Internal memory : 1024 MB
International Protection (IP) code : IP66
IP address filtering : Y
Languages support : English, Polish, Spanish, Italian, Portuguese, Turkish, Japanese, Russian, Simplified Chinese, French, Korean, Greek, Czech, Dutch, Hungarian, Swedish
Maximum aperture number : 4.4
Maximum memory card size : 256 GB
Maximum resolution : 1920 x 1080 pixels
Minimum aperture number : 1.6
Mounting type : Ceiling
Number of cameras : 1
Number of languages : 16
Number of lenses : 1
Observe distance (tele) : 768.5 m
Observe distance (wide) : 24.3 m
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : -35 - 55 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Pan preset speed : 700 °/sec
Pan range : 0 - 360°
Pan speed : 200 °/sec
Placement supported : Outdoor
Power consumption (max) : 23 W
Power consumption (typical) : 14 W
Power source type : PoE
Product colour : White
PTZ control : Y
PTZ modes : Preset sequence
Recognize distance (tele) : 384.3 m
Recognize distance (wide) : 12.1 m
Security algorithms : HTTPS, SSL/TLS, EAP-LEAP, EAP-TLS
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 95%
Storage temperature (T-T) : -50 - 60 °C
Streaming method : Multicast, Unicast
Supported graphics resolutions : 320 x 240, 640 x 360, 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080)
Tilt angle range : -15 - 90°
Tilt speed : 200 °/sec
Total megapixels : 2 MP
User access level : User
Video streaming : Y
Weight : 2.7 kg
White balance : ATW, Mercury lamp, Sodium lamp, AWC, Indoor, Outdoor, Manual
Wide Dynamic Range (WDR) : Y