

HDMI Audio/Video Extender + IR + RS232 over one Fiber (600m)



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : ATEN
Part number : VE882-AT-G
Caractéristiques :
Type : AV transmitter & receiver
HDCP : Y
3D : Y
Bandwidth : 225 MHz
Connectivity technology : Wired
DC-in jack : Y
Electrostatic Discharge (ESD) protection : 15 kV
Fiber mode structure : Multi-mode, Single-mode
Fiber optic connector : SFP
HDCP version : 1.4
HDMI in : 1
Impedance : 100
Master (outer) case gross weight : 8.66 kg
Master (outer) case height : 194 mm
Master (outer) case length : 517 mm
Master (outer) case net weight : 7.15 kg
Master (outer) case width : 292 mm
Material : Metal
Maximum refresh rate : 60 Hz
Maximum resolution : 1920 x 1080 pixels
Maximum transfer distance : 600 m
Number of HDMI outputs : 1
Operating relative humidity (H-H) : 0 - 80%
Operating temperature (T-T) : 0 - 40 °C

Operating voltage (receiver) : 5.3 V
Operating voltage (transmitter) : 5.3 V
Package depth : 283 mm
Package height : 173 mm
Package weight : 1.57 kg
Package width : 100 mm
Power consumption (RX) : 4.69 W
Power consumption (TX) : 5.8 W
Product colour : Black
Products per master (outer) case : 5 pc(s)
Rack mounting : Y
Receiver dimensions (WxDxH) : 141.7 x 103 x 30 mm
Receiver weight : 440 g
Remote (IR) input : 1
Remote (IR) output : 1
Storage relative humidity (H-H) : 0 - 80%
Storage temperature (T-T) : -20 - 60 °C
Supported video modes : 1080p
Transmitter dimensions (WxDxH) : 141.7 x 103 x 30 mm
Transmitter weight : 440 g
Weight : 1.43 kg