

BOSCH- Flexidome IP turret 5 Mps NTE-3503-F02L



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : BOSCH

Part number : NTE-3503-F02L

Représentation / réalisation :

Type : IP security camera

Réseau :

Bluetooth : N

Certification : EN 55032, CFR 47 FCC 15, B, AS/NZS CISPR 32 EN 50130-4, EN 50121-4 EN 50130-5 (IV); EN 60068-2-1, EN 60068-2-2, EN 60068-2-6, EN 60068-2-18, EN 60068-2-27, EN 60068-2-30, EN 60068-2-52, EN 60068-2-75, EN 60068-2-78, EN 60068-2-5 EN 62368-1 EN 60950-22 UL 62368-1 UL 60950-22 IEC 62471 (IR) CAN/CSA-C22.2 No. 60950-1 CAN/CSA-C22.2 No. 60950-22-07 IEC 62676-5 ITU-R BT.709-6 EN 50132-5-2 EN 62676-2 EN 62262 EN 60529 EN 50581 CE, FCC, cULus, WEEE, RCM, VCCI, EAC, CMIM

Adjustment shutter speed : Auto/Manual

Alarm input/output : Y

Angle of rotation : 270°

Back Light Compensation (BLC) : Y

Behavior analysis : Line crossing detection

Built-in HDD : N

Camera pan control : Y

Camera shutter speed : 1/25[30] - 1/15000 s

Camera shutter type : Electronic

Camera tilt control : Y

Card reader integrated : Y

Compatible memory cards : MicroSDHC, MicroSDXC

Composite video out : 1

Connectivity technology : Wired

Day/night mode : Y

DC output voltage : 12

Diameter : 13.7 cm

| |
|--|
| Ethernet interface type : Fast Ethernet |
| Ethernet LAN : Y |
| Ethernet LAN (RJ-45) ports : 1 |
| Field of view (FOV) angle : 120° |
| Form factor : Dome |
| Frame rate : 30 fps |
| Height : 135 mm |
| Housing material : Polycarbonate (PC) |
| IK code : IK10 |
| Image quality adjustment : Brightness, Contrast, Saturation, Sharpness |
| Infrared (IR) cut-off filter : Y |
| Infra-red wavelength : 850 nm |
| Intelligent Video Surveillance (IVS) system features : People counting |
| International Protection (IP) code : IP66 |
| LED type : IR |
| Maximum resolution : 3072 x 1728 pixels |
| Mirror : Y |
| Mounting type : Ceiling/wall |
| Networking standards : IEEE 802.3af, IEEE 802.3at |
| Night vision : Y |
| Night vision distance : 15 m |
| Noise reduction : Y |
| Number of cameras : 1 |
| Number of effective pixels (H x V) : 3072 x 1728 pixels |
| Number of illumination LEDs : 2 |
| Number of lenses : 1 |
| Number of sensors : 1 |
| Operating relative humidity (H-H) : 5 - 100% |
| Operating temperature (T-T) : -30 - 50 °C |
| Optical sensor size : 25.4 / 2.9 mm (1 / 2.9») |
| Pan range : 0 - 350° |
| Placement supported : Outdoor |
| Power consumption (max) : 9.5 W |
| Power consumption (Power over Ethernet (PoE)) : 10.5 W |
| Power consumption (typical) : 3.1 W |
| Power source type : DC, PoE |
| Privacy masking : Y |
| Product colour : White |
| Quality of Service (QoS) support : Y |
| Security algorithms : 128-bit AES, 256-bit AES, TLS |
| Sensor type : CMOS |
| Storage relative humidity (H-H) : 0 - 98% |
| Storage temperature (T-T) : -30 - 70 °C |
| Supported graphics resolutions : 640 x 480 (VGA), 720 x 480, 768 x 432, 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2304 x 1296, 3072 x 1728 |
| Supported network protocols : IPv4, IPv6, UDP, TCP, HTTP, HTTPS, RTP/RTCP, IGMP V2/V3, ICMP, ICMPv6, RTSP, FTP, ARP, DHCP, APIPA (Auto-IP, link local address), NTP (SNTP), SNMP (V1, V3, MIB-II), 802.1x, DNS, DNSv6, DDNS (DynDNS.org, selfHOST.de, noip.com), SMTP, iSCSI, UPnP (SSDP), DiffServ (QoS), LLDP, SOAP, Dropbox, CHAP |
| Supported video modes : 720p, 1080p |
| Sustainability certificates : CE, RoHS |
| Tilt angle range : 0 - 78° |
| Total megapixels : 5 MP |
| Video compression formats : H.264, H.265, M-JPEG |
| Video streaming : Y |

Voice codecs : AAC, G.711

Weight : 1.13 kg

White balance : Auto, Manual

Wide Dynamic Range (WDR) : Y

Wi-Fi : N