

# AC1350 wireless dual band gigabit ceiling mount access point



## DESCRIPTION

## TECHNICAL CHARACTERISTICS

Brand : TP-LINK

Part number : EAP610

### Caractéristiques :

5 GHz : Y

Airtime Fairness (ATF) : Y

### Design :

Certification : CE, FCC, RoHS

2:4 GHz : Y

AC adapter included : Y

AC input voltage : 12 V

Access Control List (ACL) : Y

Antenna type : Internal

Band steering : Y

Cabling technology : 10/100/1000Base-T(X)

DC-in jack : Y

Depth : 243 mm

Ethernet LAN (RJ-45) ports : 1

Ethernet LAN data rates : 1000 Mbit/s

Frequency band : 2.4 - 5 GHz

Harmonized System (HS) code : 85176990

Height : 64 mm

Input current : 1 A

LED indicators : Y

MAC address filtering : Y

Maximum data transfer rate : 1775 Mbit/s

Maximum data transfer rate (2:4 GHz) : 574 Mbit/s

Maximum data transfer rate (5 GHz) : 1201 Mbit/s

MIMO : Y
MIMO type : Multi User MIMO
Mounting kit : Y
Networking standards : IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Number of products included : 1 pc(s)
Operating relative humidity (H-H) : 10 - 90%
Operating temperature (T-T) : 0 - 40 °C
Package type : Box
Placement : Ceiling, Wall
Power over Ethernet (PoE) : Y
Product colour : White
Quality of Service (QoS) support : Y
Rate limiting : Y
Reset button : Y
Security algorithms : WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, WPA3, WPA3-Enterprise
Storage relative humidity (H-H) : 5 - 90%
Storage temperature (T-T) : -40 - 70 °C
Transmitting power (CE) : <20 dBm(2.4 GHz, EIRP); <23 dBm(5 GHz, EIRP)
Transmitting power (FCC) : <25 dBm (2.4 GHz); <25 dBm (5 GHz)
VLAN support : Y
Web-based management : Y
Width : 243 mm