



DESCRIPTION

The CL5716 Slideaway LCD KVM Switch series is a control unit that allows access to multiple computers from a single PS/2 or USB KVM (keyboard, video, and mouse) console. A single CL5716 can control up to 8 or 16 computers. As many as 31 additional KVM switches can be daisy-chained to the CL5716, so that up to 512 computers can all be controlled from a single KVM console.

The CL5716 offers a space-saving, streamlined approach to KVM switch technology by integrating a keyboard, 17», 17.3» or 19» LED-backlit LCD monitor, and touchpad in a 1U rack-mountable sliding housing. To enhance security, the CL5716 offers the option to use a fingerprint identification system for controlling access to both the CL5716 itself and the servers it commands.

The CL5716 is built on a modular design. The KVM section can be detached from the switch section for convenient maintenance and repair.

TECHNICAL CHARACTERISTICS

Brand : ATEN

Part number : CL5716MW-ATA-FG

AC input frequency : 50/60 Hz

AC input voltage : 100 - 240 V

Built-in display : Yes

Cables included : AC, KVM

Console ports : VGA (D-Sub)

Country of origin : China

Daisy chain : Yes

DDC2B support : Yes

Depth : 480 mm

Display : LCD

Display diagonal : 43.9 cm (17.3»)

Firmware upgradeable : Yes

Harmonized System (HS) code : 84718000

HD type : WUXGA

Height : 44 mm

Hot keys : Yes

Hot-Plug support : Yes
Hot-swap : Yes
Housing material : Metal, Plastic
Input current : 1 A
Keyboard port type : USB, PS/2
LED indicators : Yes
Linux operating systems supported : Yes
Mac operating systems supported : Yes
Manual : Yes
Master (outer) case gross weight : 16.2 kg
Master (outer) case height : 135 mm
Master (outer) case length : 833 mm
Master (outer) case width : 668 mm
Maximum resolution : 1920 x 1200 pixels
Mouse port type : USB, PS/2
Number of computers controlled : 512
On Screen Display (OSD) : Yes
Operating relative humidity (H-H) : 0 - 85%
Operating temperature (T-T) : 0 - 40 °C
Package depth : 833 mm
Package height : 135 mm
Package weight : 16.2 kg
Package width : 668 mm
Power consumption (typical) : 15.6 W
Power source : AC
Product colour : Black
Push button : Yes
Quick installation guide : Yes
Rack capacity : 1U
Rack mount kit : Yes
Rack mounting : Yes
RJ-11 ports quantity : 1
Scan interval : 1,255 s
Storage temperature (T-T) : -20 - 60 °C
VGA (D-Sub) ports quantity : 16
Video bandwidth : 60 Hz
Video port type : VGA
Weight : 13.7 kg
Width : 689.2 mm
Windows operating systems supported : Yes