

# LEGRAND UPS Keor Multiplug 600 VA



## DESCRIPTION

The Keor Multiplug is a uninterruptible power supply with interactive line technology. It delivers a rated power of 600VA and 800VA, it is CPU-controlled and is equipped, internally, with valve-regulated, hermetically sealed lead accumulator battery.

The presence of an electronic stabiliser (AVR) inside the UPS provides the connected loads with effective protection against any interference in the electrical mains.

## TECHNICAL CHARACTERISTICS

|                                              |
|----------------------------------------------|
| Brand : LEGRAND                              |
| Part number : 310083                         |
| Design :                                     |
| Certification : EN 62040-1, EN 62040-2       |
| AC outlet types : Type E                     |
| AC outlets quantity : 6 AC outlet(s)         |
| Audible alarm(s) : Y                         |
| Auto shut-off : N                            |
| Automatic Voltage Regulation (AVR) : Y       |
| Battery capacity : 7 Ah                      |
| Battery recharge time : 6 h                  |
| Battery technology : Sealed Lead Acid (VRLA) |
| Battery voltage : 12 V                       |
| Depth : 296 mm                               |
| Efficiency : 96%                             |
| Form factor : Compact                        |
| Height : 89.5 mm                             |
| Input frequency : 45/65 Hz                   |
| Input operation voltage (max) : 280 V        |
| Input operation voltage (min) : 170 V        |
| LED indicators : Y                           |
| Master (outer) case gross weight : 5.9 kg    |
| Master (outer) case height : 290 mm          |

|                                                                                |
|--------------------------------------------------------------------------------|
| Master (outer) case length : 390 mm                                            |
| Master (outer) case width : 158 mm                                             |
| Noise level : 40 dB                                                            |
| Number of input phases : 1                                                     |
| Number of output phases : 1                                                    |
| Operating relative humidity (H-H) : 0 - 95%                                    |
| Operating temperature (T-T) : 0 - 40 °C                                        |
| Output frequency : 50/60 Hz                                                    |
| Output frequency regulation : 1 Hz                                             |
| Output operation voltage (max) : 253 V                                         |
| Output operation voltage (min) : 207 V                                         |
| Output power : 360 W                                                           |
| Output power capacity : 0.6 kVA                                                |
| Output power factor : 0.6                                                      |
| Output voltage regulation : 10%                                                |
| Package depth : 5.03 mm                                                        |
| Package height : 89.5 mm                                                       |
| Package weight : 5.61 kg                                                       |
| Package width : 190 mm                                                         |
| Pallet net height : 105 cm                                                     |
| Pallet net length : 100 cm                                                     |
| Pallet net weight : 318.6 kg                                                   |
| Pallet net width : 120 cm                                                      |
| Potential-free output : N                                                      |
| Power plug : Type F                                                            |
| Power protection features : Overcharge, Overdischarge, Overload, Short circuit |
| Power source type : AC                                                         |
| Product colour : Black, White                                                  |
| Products per master (outer) case : 1 pc(s)                                     |
| Products per pallet : 54 pc(s)                                                 |
| Surge protection : Y                                                           |
| Typical backup time at full load : 15 min                                      |
| UPS topology : Line-Interactive                                                |
| USB 2:0 ports quantity : 1                                                     |
| USB port : Y                                                                   |
| USB port type : USB Type-A                                                     |
| Waveform : Sine                                                                |
| Weight : 5 kg                                                                  |
| Width : 190 mm                                                                 |